

**LEDMIRROR**

Mirror light with shaver socket 10W LED 3000K
IP44 with pull cord

DESCRIPTION

IP44 Mirror Light With Dual Voltage Shaver Socket with pull cord offering a simple upgrade to any bathroom environment the two light apertures create a soft warm lighting effect

FEATURES

- Pull cord on/off switch
- Diffused rectangle light apertures: soft lighting effect
- Permanent power to integrated dual voltage shave socket eliminates the need for separate shaver socket
- Safety isolating transformer on shaver outlet
- Please note: bathroom shaver lights are not suitable for toothbrush chargers

GENERAL INFORMATION

| | | | |
|-------------------------|----------|-----------------|---------|
| Light Source | LED | Colour / Finish | White |
| Application | Internal | Mounting Type | Surface |
| Product Warranty | 5 Years | Net Weight | 7.5 kg |
| Energy Efficiency Class | F | | |

TECHNICAL INFORMATION

| | | | |
|-------------------------------|--------|-------------------------------|----------|
| Nominal Voltage | 240 V | Frequency | 50Hz |
| Class Protection | I | Operating Temperature (Min) | -20 °C |
| Operating Temperature (Max) | 45 °C | Average Rated Life | 30,000 h |
| Number of switching cycles | 15,000 | Construction Materials Line 1 | Steel |
| Construction Materials Line 2 | Glass | Dimensions - Height | 500 mm |
| Dimensions - Width | 400 mm | Dimensions - Depth | 60 mm |

PRODUCT INFORMATION

| | | | |
|---------------------------|--------|-------------------|---------|
| Wattage Combined | 10.3W | CCT Combined | 3000K |
| Luminaire Lumens Combined | 715 lm | lm/W Combined | 69 lm/w |
| Beam Angle | 110° | CRI | 80 |
| SDCM | <6 | Lumen Maintenance | 0.8 |
| IP Rating | IP44 | | |



| PHOTOMETRICS | | | | | |
|--------------|--------------|--------|--------|------------------|---------|
| Product Code | Product Type | Watts | CCT | Luminaire lumens | Lm/W |
| LEDMIRROR | Standard | 10.3 W | 3000 K | 715 lm | 69 lm/W |

| PACKAGING | |
|------------------------------|------------|
| Packaging Type | Colour Box |
| Individual unit gross weight | 6,356 g |
| Pallet Layer Qty | 4 |
| Pallet Layers | 10 |
| Pallet Qty | 40 |
| MOM / OPQ | 1 / 1 |

