



## LEDMIRROR


Mirror light with shaver socket 10W LED 3000K IP44 with pull cord

### DESCRIPTION

IP44 Mirror Light With Dual Voltage Shaver Socket with pull cord offering a simple upgrade to any bathroom environment the two light apertures create a soft warm lighting effect

### FEATURES

- Pull cord on/off switch
- Diffused rectangle light apertures: soft lighting effect
- Permanent power to integrated dual voltage shave socket eliminates the need for separate shaver socket
- Safety isolating transformer on shaver outlet
- Please note: bathroom shaver lights are not suitable for toothbrush chargers



### GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	7.5 kg
Energy Efficiency Class	F		

### TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Steel
Construction Materials Line 2	Glass	Dimensions - Height	500 mm
Dimensions - Width	400 mm	Dimensions - Depth	60 mm
IP Rating	IP44		

### PRODUCT INFORMATION

Wattage Combined	10.3W	CCT Combined	3000K
Luminaire Lumens Combined	715 lm	lm/W Combined	69 lm/w
Beam Angle	110°	CRI	80
SDCM	<6	Lumen Maintenance	0.8





Lighting Technology used	LED	Non-Directional or Directional	NDLS
Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	Correlated Colour temperature (K) 1	3,000
Chromaticity coordinates x	0.435	Chromaticity coordinates y	0.4
Peak Luminous Intensity (cd)	270 cd	Stroboscopic effect metric (SVM)	0.9
Survival factor @6000hrs	0.9	Networked Standby Power	0.5
Displacement Factor	0.7	CCT1/WATT1: Rated Peak Intensity	270 cd





IP44

### PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
LEDMIRROR	Standard	10.3 W	3000 K	715 lm	69 lm/W

### PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	6,356 g
Pallet Layer Qty	4
Pallet Layers	10
Pallet Qty	40
MOM / OPQ	1 / 1

