

## LED Mirror Light

Polished chrome over mirror 5W LED 3000K fitting with integrated push switch




### DESCRIPTION

Contemporary designed alternative to a standard over mirror light. Available in Chrome or white to suit different design styles, integrated push switch for a sleek finish. The front opal diffuser offers well distributed light output to suit commercial and residential solutions

### FEATURES

- Vertical or horizontal mounting
- Elegantly integrated push switch
- Suitable for use in Bathroom Zone 3
- IP21 rated and insulated class 2 construction
- Available in chrome or white to compliment most bathroom decors



### GENERAL INFORMATION

Light Source	LED	Colour / Finish	Polished chrome effect
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.56 kg
Energy Efficiency Class	E		

### TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-15 °C
Operating Temperature (Max)	45 °C	Average Rated Life	25,000 h
Number of switching cycles	12,500	Construction Materials Line 1	Polycarbonate
Dimensions - Height	90 mm	Dimensions - Width	480 mm
Dimensions - Depth	50 mm	IP Rating	IP21

### PRODUCT INFORMATION

Wattage Combined	5W	CCT Combined	3000K
Luminaire Lumens Combined	530 lm	lm/W Combined	106 lm/w
Beam Angle	120°	CRI	80
SDCM	<4	Lumen Maintenance	0.9
Lighting Technology used	LED	Non-Directional or Directional	NDLS





IP21

Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	Chromaticity coordinates x	0.437
Chromaticity coordinates y	0.398	Stroboscopic effect metric (SVM)	0.0
Flicker Metric (pst)	0.0	R9 colour rendering index	15.0
Survival factor @6000hrs	0.9	Claim LED Replace Fluorescent	FALSE
Spectrum report available	Yes	Displacement Factor	0.91
CCTI/WATTI: Rated Peak Intensity	165 cd		





IP21

## PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
LEDOM5CR	Chrome	5 W	3000 K	530 lm	106 lm/W
LEDOM5WH	White	5 W	3000 K	530 lm	106 lm/W
LEDSH6CR	Chrome	6 W	3000 K	530 lm	88 lm/W
LEDSH6WH	White	6 W	3000 K	530 lm	88 lm/W

## PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	730 g
Pallet Layer Qty	100
Pallet Layers	4
Pallet Qty	400
MOM / OPQ	1 / 10

