
Spec Sheet LEDOM5WH

5 Year Warranty

IP21





LED Mirror Light

White over mirror 5W LED 3000K fitting with integrated push switch

DESCRIPTION

Contemporary designed alternative to a standard over mirror light. Available in Chrome or white to suit different design styles, integrated push switch for a sleek finish. The front opal diffuser offers well distributed light output to suit commercial and residential solutions

FEATURES

- Vertical or horizontal mounting
- Elegantly integrated push switch
- Suitable for use in Bathroom Zone 3
- IP21 rated and insulated class 2 construction
- Available in chrome or white to compliment most bathroom decors

GENERAL INFORMATION			
Light Source	LED	**Colour / Finish**	White
Application	Internal	**Mounting Type**	Surface
Product Warranty	5 Years	**Net Weight**	0.56 kg
Energy Efficiency Class	D		

TECHNICAL INFORMATION			
Nominal Voltage	240	**Frequency**	50Hz
Class Protection	2	**Operating Temperature (Min)**	-15 °C
Operating Temperature (Max)	40 °C	**Average Rated Life**	25,000 h
Number of switching cycles	12,500	**Construction Materials Line 1**	Polycarbonate
Dimensions - Height	90 mm	**Dimensions - Width**	480 mm
Dimensions - Depth	50 mm	**IP Rating**	IP21

PRODUCT INFORMATION			
Wattage Combined	5W	**CCT Combined**	3000K
Luminaire Lumens Combined	530 lm	**lm/W Combined**	106 lm/w
Beam Angle	120°	**CRI**	80
SDCM	<4	**Lumen Maintenance**	0.8
Lighting Technology used	LED	**Non-Directional or Directional**	NDLS

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

Spec Sheet LEDOM5WH

5 Year Warranty

IP21

Mains or non-mains	MLS	**Connected light source (CLS)**	FALSE
Colour tuneable light source	FALSE	**High Luminance light source**	FALSE
Anti Glare shield	FALSE	**Dimmable**	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	**Correlated Colour temperature (K) 1**	3,000
Chromaticity coordinates x	0.435	**Chromaticity coordinates y**	0.395
Peak Luminous Intensity (cd)	166 cd	**Stroboscopic effect metric (SVM)**	0.4
Flicker Metric (pst)	0.9	**R9 colour rendering index**	15
Survival factor @6000hrs	0.9	**Displacement Factor**	0.91
CCT1/WATT1: Rated Peak Intensity	166 cd		

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

5 Year Warranty

IP21

PHOTOMETRICS					
Product Code	**Product Type**	**Watts**	**CCT**	**Luminaire lumens**	**Lm/W**
LEDOM5CR	Chrome	5 W	3000 K	530 lm	106 lm/W
LEDOM5WH	White	5 W	3000 K	530 lm	106 lm/W
LEDSH6CR	Chrome	6 W	3000 K	530 lm	88 lm/W
LEDSH6WH	White	6 W	3000 K	530 lm	88 lm/W

PACKAGING	
Packaging Type	Colour Box
Individual unit gross weight	732 g
Pallet Layer Qty	100
Pallet Layers	4
Pallet Qty	400
MOM / OPQ	1 / 10

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D