Spec Sheet LEDOM5WH









White over mirror 5W LED 3000K fitting with integrated push switch

DESCRIPTION

Contemporary designed alternative to a standard over mirror light. Available in Chrome or white to suit different design styles, integrated push switch for a sleek finish. The front opal diffuser offers well distributed light output to suit commercial and residential solutions

FEATURES

- · Vertical or horizontal mounting
- Elegantly integrated push switch
- Suitable for use in Bathroom Zone 3
- IP21 rated and insulated class 2 construction
- Available in chrome or white to compliment most bathroom decors



GENERAL INFORMATION			
Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.56 kg
Energy Efficiency Class	D		

TECHNICAL INFORMATION			
Nominal Voltage	240 V	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-15 °C
Operating Temperature (Max)	40 °C	Average Rated Life	25,000 h
Number of switching cycles	12,500	Construction Materials Line 1	Polycarbonate
Dimensions - Height	90 mm	Dimensions - Width	480 mm
Dimensions - Depth	50 mm		

PRODUCT INFORMATION			
Wattage Combined	5W	CCT Combined	3000K
Luminaire Lumens Combined	525 lm	lm/W Combined	105 lm/w
Beam Angle	120°	CRI	80
SDCM	<4	Lumen Maintenance	0.8
IP Rating	IP21		













PHOTOMETRICS					
Product Code	Product Type	Watts	ССТ	Luminaire lumens	Lm/W
LEDOM5CR	Chrome	5 W	3000 K	530 lm	106 lm/W
LEDOM5WH	White	5 W	3000 K	525 lm	105 lm/W
LEDSH6CR	Chrome	6 W	3000 K	530 lm	88 lm/W
LEDSH6WH	White	6 W	3000 K	530 lm	88 lm/W

IP21	

PACKAGING		
Packaging Type	Colour Box	
Individual unit gross weight	732 g	
Pallet Layer Qty	100	
Pallet Layers	4	
Pallet Qty	400	
MOM / OPQ	1 / 10	







