



Dual Voltage Shaver Light


Dual Voltage Shaver Light 5.5W LED 3000K IP44

DESCRIPTION

Ever popular fittings offering functionality and long term performance for domestic and commercial bathrooms

FEATURES

- Dual voltage shaver socket and safety isolating transformer for bathroom use
- Permanent power to shaver socket with a pull cord switch for isolated illumination
- Access cover to connection block - easy wiring from the front of the fitting
- Optional fit chrome effect trims included
- Please note: bathroom shaver lights are not suitable for toothbrush chargers



GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	1 kg
Energy Efficiency Class	F		

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-15 °C
Operating Temperature (Max)	40 °C	Average Rated Life	25,000 h
Number of switching cycles	12,500	Construction Materials Line 1	Polycarbonate
Dimensions - Height	60 mm	Dimensions - Width	390 mm
Dimensions - Depth	65 mm		

PRODUCT INFORMATION

Wattage Combined	5.5W	CCT Combined	3000K
Luminaire Lumens Combined	410 lm	lm/W Combined	75 lm/w
Beam Angle	120°	CRI	80
SDCM	<4	Lumen Maintenance	0.9
IP Rating	IP44		





IP44

PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
LEDSH44	Standard	5.5 W	3000 K	410 lm	75 lm/W

PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	1,104 g
Intermediate Carton Depth (mm)	105 mm
Intermediate Carton Width (mm)	465 mm
Intermediate Carton Height (mm)	365 mm
Intermediate Pack Qty.	5
Pallet Layer Qty	100
Pallet Layers	4
Pallet Qty	400
MOM / OPQ	1 / 10

