









Dual Voltage Shaver Light

Dual Voltage Shaver Light 5.5W LED 3000K

DESCRIPTION

Versatile fitting offering functionality and long term performance for domestic and commercial bathrooms

FEATURES

- · Dual voltage shaver socket and safety isolating transformer
- Permanent power to shaver socket with a pull cord switch for isolated illumination
- Access cover to connection block easy wiring from the front of the fitting
- · Optional chrome effect trims included
- · Please note: bathroom shaver lights are not suitable for toothbrush chargers

	88		Jmm
			ō,
390mm	Τ.	65mm	

GENERAL INFORMATION			
Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	1 kg
Energy Efficiency Class	F		

TECHNICAL INFORMATION				
Nominal Voltage	240 V	Frequency	50Hz	
Class Protection	1	Operating Temperature (Min)	-15 °C	
Operating Temperature (Max)	40 °C	Average Rated Life	25,000 h	
Number of switching cycles	12,500	Construction Materials Line 1	Polycarbonate	
Dimensions - Height	60 mm	Dimensions - Width	390 mm	
Dimensions - Depth	65 mm			

PRODUCT INFORMATION			
Wattage Combined	5.5W	CCT Combined	3000K
Luminaire Lumens Combined	410 lm	lm/W Combined	75 lm/w
Beam Angle	120°	CRI	80
SDCM	<4	Lumen Maintenance	0.9
IP Rating	IP44		













PHOTOMETRICS					
Product Code	Product Type	Watts	ССТ	Luminaire lumens	Lm/W
LEDSH44	Standard	5.5 W	3000 K	410 lm	75 lm/W

I	P44

PACKAGING		
Packaging Type	Colour Box	
Individual unit gross weight	1,104 g	
Intermediate Carton Depth (mm)	105 mm	
Intermediate Carton Width (mm)	465 mm	
Intermediate Carton Height (mm)	365 mm	
Intermediate Pack Qty.	5	
Pallet Layer Qty	100	
Pallet Layers	4	
Pallet Qty	400	
MOM / OPQ	1 / 10	





