



## LEDSH6WH

White dual voltage shaver 6W LED 3000K fitting with integrated push switch

### DESCRIPTION

Contemporary designed alternative to a standard dual voltage shaver light. Available in Chrome or white to suit different design styles, integrated push switch and a slide off cover for the shaver connection giving a sleek finish when not in use. The front opal diffuser offers well distributed light output for practical and elegant solution

### FEATURES

- Vertical or horizontal mounting
- Elegantly integrated push switch
- Suitable for use in Bathroom Zone 3
- IP21 rated and insulated class 2 construction
- Available in chrome or white to compliment most bathroom decors
- Permanent power to shaver socket allowing use when not illuminated
- Dual voltage 110V and 240V shaver socket located under a slide to open cover maintains sleek appearance when not in use
- Bathroom shaver lights are not suitable for toothbrush chargers

### GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	1.06 kg
Energy Efficiency Class	D		

### TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-15 °C
Operating Temperature (Max)	40 °C	Average Rated Life	25,000 h
Number of switching cycles	12,500	Construction Materials Line 1	Polycarbonate
Dimensions - Height	90 mm	Dimensions - Width	480 mm
Dimensions - Depth	50 mm	IP Rating	IP21

### PRODUCT INFORMATION

Wattage Combined	6W	CCT Combined	3000K
Luminaire Lumens Combined	530 lm	lm/W Combined	88 lm/w
Beam Angle	120°	CRI	80
SDCM	<4	Lumen Maintenance	0.8
Lighting Technology used	LED	Non-Directional or Directional	NDLS





Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	Correlated Colour temperature (K) 1	3,000
Chromaticity coordinates x	0.434	Chromaticity coordinates y	0.394
Peak Luminous Intensity (cd)	166 cd	Stroboscopic effect metric (SVM)	0.4
Flicker Metric (pst)	1	R9 colour rendering index	15
Survival factor @6000hrs	0.9	Networked Standby Power	0
Displacement Factor	0.91	CCT1/WATT1: Rated Peak Intensity	166 cd





IP21

## PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
LEDOM5CR	Chrome	5 W	3000 K	530 lm	106 lm/W
LEDOM5WH	White	5 W	3000 K	530 lm	106 lm/W
LEDSH6CR	Chrome	6 W	3000 K	530 lm	88 lm/W
LEDSH6WH	White	6 W	3000 K	530 lm	88 lm/W

## PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	1,135 g
Pallet Layer Qty	100
Pallet Layers	4
Pallet Qty	400
MOM / OPQ	1 / 10

