



IP65 LED Emergency Twinspot


IP65 LED emergency white twin spot 2 x 3W
220lm LED 6000K

DESCRIPTION

IP65 emergency twin spot with adjustable heads compact and robust fitting offering two 3W outputs delivering emergency lighting where required in commercial and industrial applications

FEATURES

- Twin 3W LED projectors: provide superior light output to traditional twinspot fittings
- IP65 rating utilising high quality polycarbonate enclosure: for installation in wet or dusty environments
- Horizontally and vertically adjustable heads, 180° rotation across the horizontal plane
- Reduced battery capacity requirement: allows a more compact design reducing the weight dramatically compared to traditional products facilitating easier installation
- Individual indicator to show healthy charge to battery
- 3 hour non-maintained function
- Ni-Cd 3.6V 6Ah battery 1 year warranty - Replacement battery code: EB3



GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal/External	Mounting Type	Surface
Product Warranty	5 Years	Battery Warranty	1 Year
Net Weight	2.36 kg		

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	40 °C
Operating Temperature (Max)	-10 °C	Average Rated Life	30,000 h
Construction Materials Line 1	Polycarbonate	Dimensions - Height	295 mm
Dimensions - Width	300 mm	Dimensions - Depth	70 mm
IK Rating	IK08	IP Rating	IP65

PRODUCT INFORMATION

Wattage Combined	7W	CCT Combined	6000K
Luminaire Lumens Combined	460 lm	lm/W Combined	66 lm/w
Beam Angle	120°	CRI	80
Emergency Lumen Output	441 lm	Dimmable	Not Dimmable



PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
LEDTWNSPOT	Emergency	7	6000 K	460 lm	66 lm/W



IP65



IK08

ACCESSORIES		
Product Code	Description	MOM / OPQ
EB3	Ni-Cd 3.6V 6Ah Side-by-side Battery	1 / 1

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	1,828 g
Pallet Layer Qty	36
Pallet Layers	4
Pallet Qty	144
MOM / OPQ	1 / 6

