



13W LED Linkable CCT Strip Light


Linkable 849mm linear under cabinet LED strip light 13W CCT selectable

DESCRIPTION

High quality linkable LED cabinet lights inclusive of accessories for easy installation. Use the sliding switch to choose between warm, cool or daylight white light to suit the requirement or preference. Low energy consumption and long lifetime makes the LINKCS range the optimal choice for stylish and effective task lighting

FEATURES

- Superb light output and distribution, with opal diffuser for a soft effect - perfect for task lighting
- Easily select between warm white, cool white or day light via a simple switch to suit the application or preference
- Link a maximum of 12 fittings end-to-end for a continuous line, or space apart with the 30cm link lead (included)
- Safe and simple connectivity thanks to the dual polarity of the 2 pins at each end
- Simple rocker switch for local on/off control
- Fitting comes with a 1.8m mains lead, 30cm link lead, and integral plug & sockets for simple and easy connection (no driver required). Additional 50cm link lead accessory: product



GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.53 kg
Energy Efficiency Class	F		

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	20,000 h
Number of switching cycles	12,500	Construction Materials Line 1	Polycarbonate
Dimensions - Height	30 mm	Dimensions - Width	849 mm
Dimensions - Depth	22 mm	IP Rating	IP20

PRODUCT INFORMATION

Wattage Combined	13W	CCT Combined	3000K / 4200K / 6500K
Luminaire Lumens Combined	1264 - 1295 lm	lm/W Combined	97 - 100 lm/w
Beam Angle	130°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
Lighting Technology used	LED	Non-Directional or Directional	NDLS



Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Displacement Factor	0.5	CCT1/WATTI: Rated Peak Intensity	97.23 cd
CCT2/WATTI: Rated Peak Intensity	98.46 cd	CCT3/WATTI: Rated Peak Intensity	99.61 cd



IP20



Colour Temp.
Selectable





IP20



Colour Temp.
Selectable

PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
LINKCS13	849mm	13 W	3000 K	1264 lm	97 lm/W
			4200 K	1280 lm	98 lm/W
			6500 K	1295 lm	100 lm/W
LINKCS4	288mm	4 W	3000 K	380 lm	95 lm/W
			4200 K	385 lm	96 lm/W
			6500 K	390 lm	98 lm/W
LINKCS9	549mm	9 W	3000 K	896 lm	100 lm/W
			4200 K	901 lm	100 lm/W
			6500 K	905 lm	101 lm/W

ACCESSORIES

Product Code	Description	MOM / OPQ
LINKL05	50CM Link lead for LINKCS range	1 / 5

PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	329 g
Intermediate Carton Depth (mm)	195 mm
Intermediate Carton Width (mm)	870 mm
Intermediate Carton Height (mm)	125 mm
Intermediate Pack Qty.	10
Pallet Layer Qty	80
Pallet Layers	6
Pallet Qty	480
MOM / OPQ	1 / 10

