Spec Sheet LINKCS4


eterna.

5 Year Warranty

IP20

Colour Temp. Selectable





4W LED Linkable CCT Strip Light

Linkable 288mm linear under cabinet LED strip light 4W CCT selectable

DESCRIPTION

High quality linkable LED cabinet lights inclusive of accessories for easy installation. Use the sliding switch to choose between warm, cool or daylight white light to suit the requirement or preference. Low energy consumption and long lifetime makes the LINKCS range the optimal choice for stylish and effective task lighting

FEATURES

- Superb light output and distribution, with opal diffuser for a soft effect - perfect for task lighting
- Easily select between warm white, cool white or day light via a simple switch to suit the application or preference
- Link a maximum of 12 fittings end-to-end for a continuous line, or space apart with the 30cm link lead (included)
- Safe and simple connectivity thanks to the dual polarity of the 2 pins at each end
- Simple rocker switch for local on/off control
- Fitting comes with a 1.8m mains lead, 30cm link lead, and integral plug & sockets for simple and easy connection (no driver required). Additional 50cm link lead accessory: product

GENERAL INFORMATION			
Light Source	LED	**Colour / Finish**	White
Application	Internal	**Mounting Type**	Surface
Product Warranty	5 Years	**Net Weight**	0.58 kg
Energy Efficiency Class	F		

TECHNICAL INFORMATION			
Nominal Voltage	240	**Frequency**	50Hz
Class Protection	2	**Operating Temperature (Min)**	-20 °C
Operating Temperature (Max)	45 °C	**Average Rated Life**	20,000 h
Number of switching cycles	12,500	**Construction Materials Line 1**	Polycarbonate
Dimensions - Height	30 mm	**Dimensions - Width**	288 mm
Dimensions - Depth	22 mm	**IP Rating**	IP20

PRODUCT INFORMATION			
Wattage Combined	4W	**CCT Combined**	3000K / 4200K / 6500K
Luminaire Lumens Combined	380 - 390 lm	**lm/W Combined**	95 - 98 lm/w
Beam Angle	130°	**CRI**	80
SDCM	<6	**Lumen Maintenance**	0.7
Lighting Technology used	LED	**Non-Directional or Directional**	NDLS

CE

UKCA

Member of theLIA

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

Spec Sheet LINKCS4

Mains or non-mains	MLS	**Connected light source (CLS)**	FALSE
Colour tuneable light source	FALSE	**High Luminance light source**	FALSE
Anti Glare shield	FALSE	**Dimmable**	Not Dimmable
Displacement Factor	0.5	**CCT1/WATT1: Rated Peak Intensity**	95 cd
CCT2/WATT1: Rated Peak Intensity	96.25 cd	**CCT3/WATT1: Rated Peak Intensity**	97.5 cd

5 Year Warranty

IP20

Colour Temp. Selectable

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

PHOTOMETRICS					
Product Code	**Product Type**	**Watts**	**CCT**	**Luminaire lumens**	**Lm/W**
LINKCS13	849mm	13 W	3000 K	1264 lm	97 lm/W
			4200 K	1280 lm	98 lm/W
			6500 K	1295 lm	100 lm/W
LINKCS4	288mm	4 W	3000 K	380 lm	95 lm/W
			4200 K	385 lm	96 lm/W
			6500 K	390 lm	98 lm/W
LINKCS9	549mm	9 W	3000 K	896 lm	100 lm/W
			4200 K	901 lm	100 lm/W
			6500 K	905 lm	101 lm/W

ACCESSORIES		
Product Code	**Description**	**MOM / OPQ**
LINKL05	50CM Link lead for LINKCS range	1 / 5

PACKAGING	
Packaging Type	Colour Box
Individual unit gross weight	214 g
Intermediate Carton Depth (mm)	195 mm
Intermediate Carton Width (mm)	318 mm
Intermediate Carton Height (mm)	130 mm
Intermediate Pack Qty.	10
Pallet Layer Qty	270
Pallet Layers	5
Pallet Qty	1,350
MOM / OPQ	1 / 10