



9W LED Linkable CCT Strip Light

Linkable 549mm linear under cabinet LED strip light 9W CCT selectable

DESCRIPTION

High quality linkable LED cabinet lights inclusive of accessories for easy installation. Use the sliding switch to choose between warm, cool or daylight white light to suit the requirement or preference. Low energy consumption and long lifetime makes the LINKCS range the optimal choice for stylish and effective task lighting

FEATURES

- Superb light output and distribution, with opal diffuser for a soft effect – perfect for task lighting
- Easily select between warm white, cool white or day light via a simple switch to suit the application or preference
- Link a maximum of 12 fittings end-to-end for a continuous line, or space apart with the 30cm link lead (included)
- Safe and simple connectivity thanks to the dual polarity of the 2 pins at each end
- Simple rocker switch for local on/off control
- Fitting comes with a 1.8m mains lead, 30cm link lead, and integral plug & sockets for simple and easy connection (no driver required). Additional 50cm link lead accessory: product code: LINKL05

GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.69 kg
Energy Efficiency Class	F		

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	20,000 h
Number of switching cycles	12,500	Construction Materials Line 1	Polycarbonate
Dimensions - Height	30 mm	Dimensions - Width	549 mm
Dimensions - Depth	22 mm		

PRODUCT INFORMATION

Wattage Combined	9W	CCT Combined	3000K / 4200K / 6500K
Luminaire Lumens Combined	896 - 905 lm	lm/W Combined	100 - 101 lm/w
Beam Angle	130°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP20		





PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
LINKCS13	Standard	13 W	3000 K	1264 lm	97 lm/W
			4200 K	1280 lm	98 lm/W
			6500 K	1295 lm	100 lm/W
LINKCS4	Standard	4 W	3000 K	380 lm	95 lm/W
			4200 K	385 lm	96 lm/W
			6500 K	390 lm	98 lm/W
LINKCS9	Standard	9 W	3000 K	896 lm	100 lm/W
			4200 K	901 lm	100 lm/W
			6500 K	905 lm	101 lm/W

ACCESSORIES		
Product Code	Description	MOM / OPQ
LINKL05	50CM Link lead for LINKCS range	1 / 5

PACKAGING	
Packaging Type	Colour Box
Individual unit gross weight	269 g
Intermediate Carton Depth (mm)	195 mm
Intermediate Carton Width (mm)	570 mm
Intermediate Carton Height (mm)	128 mm
Intermediate Pack Qty.	10
Pallet Qty	0
MOM / OPQ	1 / 10

