



9W LED Linkable CCT Strip Light


Linkable 549mm linear under cabinet LED strip light 9W CCT selectable

DESCRIPTION

High quality linkable LED cabinet lights inclusive of accessories for easy installation. Use the sliding switch to choose between warm, cool or daylight white light to suit the requirement or preference. Low energy consumption and long lifetime makes the LINKCS range the optimal choice for stylish and effective task lighting

FEATURES

- Superb light output and distribution, with opal diffuser for a soft effect - perfect for task lighting
- Easily select between warm white, cool white or day light via a simple switch to suit the application or preference
- Link a maximum of 12 fittings end-to-end for a continuous line, or space apart with the 30cm link lead (included)
- Safe and simple connectivity thanks to the dual polarity of the 2 pins at each end
- Simple rocker switch for local on/off control
- Fitting comes with a 1.8m mains lead, 30cm link lead, and integral plug & sockets for simple and easy connection (no driver required). Additional 50cm link lead accessory: product



GENERAL INFORMATION

| | | | |
|-------------------------|----------|-----------------|---------|
| Light Source | LED | Colour / Finish | White |
| Application | Internal | Mounting Type | Surface |
| Product Warranty | 5 Years | Net Weight | 0.69 kg |
| Energy Efficiency Class | F | | |

TECHNICAL INFORMATION

| | | | |
|-----------------------------|--------|-------------------------------|---------------|
| Nominal Voltage | 240 | Frequency | 50Hz |
| Class Protection | 2 | Operating Temperature (Min) | -20 °C |
| Operating Temperature (Max) | 45 °C | Average Rated Life | 20,000 h |
| Number of switching cycles | 12,500 | Construction Materials Line 1 | Polycarbonate |
| Dimensions - Height | 30 mm | Dimensions - Width | 549 mm |
| Dimensions - Depth | 22 mm | IP Rating | IP20 |

PRODUCT INFORMATION

| | | | |
|---------------------------|--------------|--------------------------------|-----------------------|
| Wattage Combined | 9W | CCT Combined | 3000K / 4200K / 6500K |
| Luminaire Lumens Combined | 896 - 905 lm | lm/W Combined | 100 - 101 lm/w |
| Beam Angle | 130° | CRI | 80 |
| SDCM | <6 | Lumen Maintenance | 0.7 |
| Lighting Technology used | LED | Non-Directional or Directional | NDLS |



| | | | |
|----------------------------------|-----------|----------------------------------|--------------|
| Mains or non-mains | MLS | Connected light source (CLS) | FALSE |
| Colour tuneable light source | FALSE | High Luminance light source | FALSE |
| Anti Glare shield | FALSE | Dimmable | Not Dimmable |
| Displacement Factor | 0.5 | CCT1/WATTI: Rated Peak Intensity | 99.55 cd |
| CCT2/WATTI: Rated Peak Intensity | 100.11 cd | CCT3/WATTI: Rated Peak Intensity | 100.55 cd |



IP20



Colour Temp.
Selectable





IP20



Colour Temp.
Selectable

PHOTOMETRICS

| Product Code | Product Type | Watts | CCT | Luminaire lumens | Lm/W |
|--------------|--------------|-------|--------|------------------|----------|
| LINKCS13 | 849mm | 13 W | 3000 K | 1264 lm | 97 lm/W |
| | | | 4200 K | 1280 lm | 98 lm/W |
| | | | 6500 K | 1295 lm | 100 lm/W |
| LINKCS4 | 288mm | 4 W | 3000 K | 380 lm | 95 lm/W |
| | | | 4200 K | 385 lm | 96 lm/W |
| | | | 6500 K | 390 lm | 98 lm/W |
| LINKCS9 | 549mm | 9 W | 3000 K | 896 lm | 100 lm/W |
| | | | 4200 K | 901 lm | 100 lm/W |
| | | | 6500 K | 905 lm | 101 lm/W |

ACCESSORIES

| Product Code | Description | MOM / OPQ |
|--------------|---------------------------------|-----------|
| LINKL05 | 50CM Link lead for LINKCS range | 1 / 5 |

PACKAGING

| | |
|---------------------------------|------------|
| Packaging Type | Colour Box |
| Individual unit gross weight | 269 g |
| Intermediate Carton Depth (mm) | 195 mm |
| Intermediate Carton Width (mm) | 570 mm |
| Intermediate Carton Height (mm) | 128 mm |
| Intermediate Pack Qty. | 10 |
| Pallet Layer Qty | 160 |
| Pallet Layers | 4 |
| Pallet Qty | 640 |
| MOM / OPQ | 1 / 10 |

