



Link Lead for LINKCS Range

0.5m white link lead for use with the LINKCS range

DESCRIPTION

High quality linkable LED cabinet lights inclusive of accessories for easy installation. Use the sliding switch to choose between warm, cool or daylight white light to suit the requirement or preference. Low energy consumption and long lifetime makes the LINKCS range the optimal choice for stylish and effective task lighting

| GENERAL INFORMATION | | | |
|-------------------------------|--------|-------------|----------|
| Colour / Finish | White | Application | Internal |
| Product Warranty | 1 Year | Net Weight | 0.06 kg |
| TECHNICAL INFORMATION | | | |
| Nominal Voltage | 240 | Frequency | 50Hz |
| Construction Materials Line 1 | PVC | IP Rating | IP20 |
| PRODUCT INFORMATION | | | |
| Connected light source (CLS) | FALSE | | |





IP20

PACKAGING

| | |
|--|------------|
| Packaging Type | Colour Box |
| Individual unit gross weight | 51 g |
| Intermediate Carton Depth (mm) | 178 mm |
| Intermediate Carton Width (mm) | 175 mm |
| Intermediate Carton Height (mm) | 70 mm |
| Intermediate Pack Qty. | 10 |
| Pallet Layer Qty | 1,800 |
| Pallet Layers | 2 |
| Pallet Qty | 3,600 |
| MOM / OPQ | 1 / 5 |

