
Spec Sheet MINIEYEBK

eterna.

5 Year Warranty

IP66





Sparrowhawk

Mini Sparrowhawk circular black eyelid IP66 amenity bulkhead opal diffuser 6W LED 4200K

DESCRIPTION

Long life, energy efficient utility fitting perfect for domestic or commercial settings including pathway illumination, gardens and porches, staircases and many more.

FEATURES

- Multiple low power LED array & optically optimised diffuser - ensures a soft, even lighting effect with no degradation of light output
- IP66 ceiling or wall mounted: giving versatile fixing options suitable for bathroom, internal and external use
- Polycarbonate construction. Stainless steel screws
- 4200K colour temperature for bright neutral white appearance

GENERAL INFORMATION			
Light Source	LED	**Colour / Finish**	Black
Application	Internal/External	**Mounting Type**	Surface
Product Warranty	5 Years	**Net Weight**	0.3 kg
Energy Efficiency Class	E		

TECHNICAL INFORMATION			
Nominal Voltage	240	**Frequency**	50Hz
Class Protection	2	**Operating Temperature (Min)**	-20 °C
Operating Temperature (Max)	45 °C	**Average Rated Life**	50,000 h
Number of switching cycles	25,000	**Construction Materials Line 1**	Polycarbonate
Dimensions - Height	200 mm	**Dimensions - Width**	200 mm
Dimensions - Depth	80 mm	**IP Rating**	IP66

PRODUCT INFORMATION			
Wattage Combined	6W	**CCT Combined**	4200K
Luminaire Lumens Combined	445 lm	**lm/W Combined**	74 lm/w
Beam Angle	120°	**CRI**	80
SDCM	<6	**Lumen Maintenance**	0.8
Lighting Technology used	LED	**Non-Directional or Directional**	NDLS

CE

UKCA

Member of theLIA

Spec Sheet MINIEYEBK

5 Year Warranty

IP66

Mains or non-mains	MLS	**Connected light source (CLS)**	FALSE
Colour tuneable light source	FALSE	**High Luminance light source**	FALSE
Anti Glare shield	FALSE	**Correlated Colour temperature type**	SINGLE_VALUE
Correlated Colour temperature (K) 1	4,200	**Chromaticity coordinates x**	0.382
Chromaticity coordinates y	0.374	**Stroboscopic effect metric (SVM)**	0.9
Flicker Metric (pst)	0.5	**R9 colour rendering index**	20.0
Survival factor @6000hrs	0.9	**Claim LED Replace Fluorescent**	FALSE
Spectrum report available	Yes	**Displacement Factor**	0.9
CCT1/WATT1: Rated Peak Intensity	103 cd		

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

PHOTOMETRICS					
Product Code	**Product Type**	**Watts**	**CCT**	**Luminaire lumens**	**Lm/W**
MINIEYEBK	Standard	6 W	4200 K	445 lm	74 lm/W
MINIFULLWH	Standard	6 W	4200 K	530 lm	88 lm/W

PACKAGING	
Packaging Type	Colour Box
Individual unit gross weight	368 g
Pallet Layer Qty	100
Pallet Layers	3
Pallet Qty	300
MOM / OPQ	1 / 10