



## Sparrowhawk


Mini Sparrowhawk circular white IP66 amenity bulkhead opal diffuser 6W LED 4200K

### DESCRIPTION

Long life, energy efficient utility fitting perfect for domestic or commercial settings including pathway illumination, gardens and porches, staircases and many more.

### FEATURES

- Multiple low power LED array & optically optimised diffuser - ensures a soft, even lighting effect with no degradation of light output
- IP66 ceiling or wall mounted: giving versatile fixing options suitable for bathroom, internal and external use
- Polycarbonate construction. Stainless steel screws
- 4200K colour temperature for bright neutral white appearance



### GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal/External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.3 kg
Energy Efficiency Class	E		

### TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	50,000 h
Number of switching cycles	2,500	Construction Materials Line 1	Polycarbonate
Dimensions - Height	215 mm	Dimensions - Width	215 mm
Dimensions - Depth	80 mm	IP Rating	IP66

### PRODUCT INFORMATION

Wattage Combined	6W	CCT Combined	4200K
Luminaire Lumens Combined	530 lm	lm/W Combined	88 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.8
Lighting Technology used	LED	Non-Directional or Directional	NDLS





IP66

Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Correlated Colour temperature type	SINGLE_VALUE
Correlated Colour temperature (K) 1	4,200	Chromaticity coordinates x	0.381
Chromaticity coordinates y	0.378	Stroboscopic effect metric (SVM)	0.4
Flicker Metric (pst)	0.5	R9 colour rendering index	16.0
Survival factor @6000hrs	0.9	Claim LED Replace Fluorescent	FALSE
Spectrum report available	Yes	Displacement Factor	0.9
CCTI/WATTI: Rated Peak Intensity	153 cd		





IP66

## PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
MINIEYBK	Standard	6 W	4200 K	445 lm	74 lm/W
MINIFULLWH	Standard	6 W	4200 K	530 lm	88 lm/W

## PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	364 g
Pallet Layer Qty	100
Pallet Layers	3
Pallet Qty	300
MOM / OPQ	1 / 10

