



Sparrowhawk


Mini Sparrowhawk circular white IP66 amenity bulkhead opal diffuser 6W LED 4200K

DESCRIPTION

Long life, energy efficient utility fitting perfect for domestic or commercial settings including pathway illumination, gardens and porches, staircases and many more.

FEATURES

- Multiple low power LED array & optically optimised diffuser - ensures a soft, even lighting effect with no degradation of light output
- IP66 ceiling or wall mounted: giving versatile fixing options suitable for bathroom, internal and external use
- Polycarbonate construction. Stainless steel screws
- 4200K colour temperature for bright neutral white appearance



GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal/External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.3 kg
Energy Efficiency Class	E		

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	50,000 h
Number of switching cycles	2,500	Construction Materials Line 1	Polycarbonate
Dimensions - Height	215 mm	Dimensions - Width	215 mm
Dimensions - Depth	80 mm	IP Rating	IP66

PRODUCT INFORMATION

Wattage Combined	6W	CCT Combined	4200K
Luminaire Lumens Combined	530 lm	lm/W Combined	88 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.8
Lighting Technology used	LED	Non-Directional or Directional	NDLS





Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Correlated Colour temperature type	SINGLE_VALUE
Correlated Colour temperature (K) 1	4,200	Chromaticity coordinates x	0.381
Chromaticity coordinates y	0.378	Stroboscopic effect metric (SVM)	0.4
Flicker Metric (pst)	0.5	R9 colour rendering index	16.0
Survival factor @6000hrs	0.9	Claim LED Replace Fluorescent	FALSE
Spectrum report available	Yes	Displacement Factor	0.9
CCTI/WATTI: Rated Peak Intensity	153 cd		





PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
MINIEYBK	Standard	6	4200 K	445 lm	74 lm/W
MINIFULLWH	Standard	6	4200 K	530 lm	88 lm/W

PACKAGING	
Packaging Type	Colour Box
Individual unit gross weight	364 g
Pallet Layer Qty	100
Pallet Layers	3
Pallet Qty	300
MOM / OPQ	1 / 10

