



IP44




## 6W LED Lantern

6W 3100K LED White Lantern

### DESCRIPTION

Energy efficient, modern design LED lantern in white offers evenly diffused warm lighting effect



### GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	External	Mounting Type	Surface
Product Warranty	2 Years	Net Weight	0.4 kg
Energy Efficiency Class	G		

### TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50-60Hz
Class Protection	1	Average Rated Life	35,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	240 mm	Dimensions - Width	170 mm
Dimensions - Depth	200 mm	IP Rating	IP44

### PRODUCT INFORMATION

Wattage Combined	6W	CCT Combined	3100K
Luminaire Lumens Combined	330 lm	lm/W Combined	55 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
Lighting Technology used	LED	Non-Directional or Directional	NDLS
Mains or non-mains	MLS	Connected light source (CLS)	FALSE



Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
CCT1/WATT1: Rated Peak Intensity	120 cd		



IP44





IP44

## PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
MODERNOBK	Black	6 W	3100 K	330 lm	55 lm/W
MODERNOWH	White	6 W	3100 K	330 lm	55 lm/W
MODPIRWH	PIR	6 W	3100 K	330 lm	55 lm/W

## PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	641 g
Pallet Layer Qty	24
Pallet Layers	5
Pallet Qty	120
MOM / OPQ	1 / 6

