



Carina



Carina white IP65 bulkhead 17W CCT selectable with microwave sensor

DESCRIPTION

Versatile range of decorative bulkheads, offering practicality and style with multiple functional options - perfect for superior leisure, hotels & outdoor applications

FEATURES

- Polycarbonate construction
- Full circular LED array
- IP65, ceiling or wall mounted
- Full circular LED array
- Colour temperature selectable 3100K, 4200K & 6400K
- Plug in connector between the terminal block and the gear tray. Terminal block is located on the base, allowing for easy wiring and the gear tray to be removed during installation
- Adjustable microwave sensor with options to adjust 2-50 lux or disable, detection range 10-100% and time 5 secs - 30 mins



GENERAL INFORMATION

| | | | |
|-------------------------|-------------------|-----------------|---------|
| Light Source | LED | Colour / Finish | White |
| Application | Internal/External | Mounting Type | Surface |
| Product Warranty | 5 Years | Net Weight | 1.19 kg |
| Energy Efficiency Class | E | | |

TECHNICAL INFORMATION

| | | | |
|-----------------------------|--------|-------------------------------|---------------|
| Nominal Voltage | 240 V | Frequency | 50Hz |
| Class Protection | 2 | Operating Temperature (Min) | 0 °C |
| Operating Temperature (Max) | 45 °C | Average Rated Life | 50,000 h |
| Number of switching cycles | 25,000 | Construction Materials Line 1 | Polycarbonate |
| Dimensions - Height | 325 mm | Dimensions - Width | 325 mm |
| Dimensions - Depth | 110 mm | | |

PRODUCT INFORMATION

| | | | |
|---------------------------|----------------|-------------------|-----------------------|
| Wattage Combined | 17W | CCT Combined | 3100K / 4200K / 6400K |
| Luminaire Lumens Combined | 1480 - 1500 lm | lm/W Combined | 87 - 88 lm/w |
| Beam Angle | 120° | CRI | 80 |
| SDCM | <6 | Lumen Maintenance | 0.8 |
| IP Rating | IP65 | IK Rating | IK08 |



| PHOTOMETRICS | | | | | |
|--------------|-------------------------------------|-------|--------|------------------|---------|
| Product Code | Product Type | Watts | CCT | Luminaire lumens | Lm/W |
| CSLEDCR | Standard,Chrome | 17 W | 3000 K | 1480 lm | 87 lm/W |
| | | | 4200 K | 1580 lm | 93 lm/W |
| | | | 6400 K | 1500 lm | 88 lm/W |
| CSLEDCREM3 | Emergency,Chrome | 17 W | 3100 K | 1480 lm | 87 lm/W |
| | | | 4200 K | 1580 lm | 93 lm/W |
| | | | 6400 K | 1500 lm | 88 lm/W |
| CSLEDWH | Standard,White | 17 W | 3000 K | 1480 lm | 87 lm/W |
| | | | 4200 K | 1580 lm | 93 lm/W |
| | | | 6400 K | 1500 lm | 88 lm/W |
| CSLEDWHEM3 | Emergency,White | 17 W | 3000 K | 1480 lm | 87 lm/W |
| | | | 4200 K | 1580 lm | 93 lm/W |
| | | | 6400 K | 1500 lm | 88 lm/W |
| MSCSLCREM3 | Emergency,On / Off Microwave,Chrome | 17 W | 3100 K | 1480 lm | 87 lm/W |
| | | | 4200 K | 1580 lm | 93 lm/W |
| | | | 6400 K | 1500 lm | 88 lm/W |
| MSCSLEDCR | On / Off Microwave,Chrome | 17 W | 3100 K | 1480 lm | 87 lm/W |
| | | | 4200 K | 1580 lm | 93 lm/W |
| | | | 6400 K | 1500 lm | 88 lm/W |
| MSCSLEDWH | On / Off Microwave,White | 17 W | 3100 K | 1480 lm | 87 lm/W |
| | | | 4200 K | 1580 lm | 93 lm/W |
| | | | 6400 K | 1500 lm | 88 lm/W |
| MSCSLWHEM3 | Emergency,On / Off Microwave,White | 17 W | 3100 K | 1480 lm | 87 lm/W |
| | | | 4200 K | 1580 lm | 93 lm/W |
| | | | 6400 K | 1500 lm | 88 lm/W |
| SDCSLCREM3 | Emergency,Step Dim Microwave,Chrome | 17 W | 3100 K | 1480 lm | 87 lm/W |
| | | | 4200 K | 1580 lm | 93 lm/W |
| | | | 6400 K | 1500 lm | 88 lm/W |
| SDCSLEDCR | Step Dim Microwave,Chrome | 17 W | 3100 K | 1480 lm | 87 lm/W |
| | | | 4200 K | 1580 lm | 93 lm/W |
| | | | 6400 K | 1500 lm | 88 lm/W |
| SDCSLEDWH | Step Dim Microwave,White | 17 W | 3100 K | 1480 lm | 87 lm/W |
| | | | 4200 K | 1580 lm | 93 lm/W |
| | | | 6400 K | 1500 lm | 88 lm/W |
| SDCSLWHEM3 | Emergency,Step Dim Microwave,White | 17 W | 3100 K | 1480 lm | 87 lm/W |
| | | | 4200 K | 1580 lm | 93 lm/W |
| | | | 6400 K | 1500 lm | 88 lm/W |

| ACCESSORIES | | |
|--------------|------------------------------|-----------|
| Product Code | Description | MOM / OPQ |
| CFTCR | Chrome Trim for Carina Range | 1 / 50 |

| PACKAGING | |
|------------------------------|------------|
| Packaging Type | Colour Box |
| Individual unit gross weight | 1,071 g |
| Pallet Layer Qty | 24 |
| Pallet Layers | 4 |
| Pallet Qty | 96 |
| MOM / OPQ | 1 / 8 |



IP65



IK08



Colour Temp. Selectable

