Spec Sheet OMLED10











LED Over Mirror Light

Over mirror light 10W LED 3000K with opal diffuser and pull cord

DESCRIPTION

This stylish fitting is the perfect solution to provide additional task lighting in many applications. The fitting provides excellent light output and is a superb energy efficient and long life alternative to fluorescent products.

FEATURES

- · Aluminium base and PMMA diffuser
- Primarily designed for bathrooms, but equally useful for many other applications
- · Pull cord on/off switch
- 3000K warm colour temperature: offering a pleasing lighting appearance
- · Sleek modern design

				[[
۰	435mm (ŗ	55mm	m

GENERAL INFORMATION			
Light Source	LED	Colour / Finish	Matt silver effect
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.4 kg
Energy Efficiency Class	F		

TECHNICAL INFORMATION			
Nominal Voltage	240 V	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-15 °C
Operating Temperature (Max)	45 °C	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Aluminium base
Construction Materials Line 2	PMMA diffuser	Dimensions - Height	36 mm
Dimensions - Width	435 mm	Dimensions - Depth	55 mm

PRODUCT INFORMATION			
Wattage Combined	10W	CCT Combined	3000K
Luminaire Lumens Combined	1010 lm	lm/W Combined	101 lm/w
Beam Angle	120°	CRI	80
SDCM	<4	Lumen Maintenance	0.7
IP Rating	IP44		













PHOTOMETRICS					
Product Code	Product Type	Watts	сст	Luminaire lumens	Lm/W
OMLED10	Standard	10 W	3000 K	1010 lm	101 lm/W

IP44	

PACKAGING		
Packaging Type	Colour Box	
Individual unit gross weight	351 g	
Pallet Layer Qty	200	
Pallet Layers	4	
Pallet Qty	800	
MOM / OPQ	1 / 20	







