



LED Over Mirror Light


Over mirror light 10W LED 3000K with opal diffuser and pull cord

DESCRIPTION

This stylish fitting is the perfect solution to provide additional task lighting in many applications. The fitting provides excellent light output and is a superb energy efficient and long life alternative to fluorescent products.

FEATURES

- Aluminium base and PMMA diffuser
- Primarily designed for bathrooms, but equally useful for many other applications
- Pull cord on/off switch
- 3000K warm colour temperature: offering a pleasing lighting appearance
- Sleek modern design



GENERAL INFORMATION

Light Source	LED	Colour / Finish	Matt silver effect
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.4 kg
Energy Efficiency Class	F		

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-15 °C
Operating Temperature (Max)	45 °C	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Aluminium base
Construction Materials Line 2	PMMA diffuser	Dimensions - Height	36 mm
Dimensions - Width	435 mm	Dimensions - Depth	55 mm
IP Rating	IP44		

PRODUCT INFORMATION

Wattage Combined	10W	CCT Combined	3000K
Luminaire Lumens Combined	1010 lm	lm/W Combined	101 lm/w
Beam Angle	120°	CRI	80
SDCM	<4	Lumen Maintenance	0.7



Lighting Technology used	LED	Non-Directional or Directional	NDLS
Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Correlated Colour temperature (K) 1	3,000	Displacement Factor	0.93
CCTI/WATTI: Rated Peak Intensity	299 cd		



IP44





IP44

PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
OMLED10	Standard	10 W	3000 K	1010 lm	101 lm/W

PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	351 g
Pallet Layer Qty	200
Pallet Layers	4
Pallet Qty	800
MOM / OPQ	1 / 20

