Spec Sheet PACIFIC12









Polished chrome ceiling/wall light 12W 800lm

DESCRIPTION

LED 3100K IP44

The stylish fitting is ideal for installtion in a mulitude of situations. Ceiling or wall mounted in a domestic or commercial setting and suitable for bathrooms. Long life, energy efficient alternative to traditional fluorescent luminaires

FEATURES

- Multiple low power LED array & optically optimised diffuser ensures a soft, even lighting effect with no degradation of light
- · Corrosion resistant stainless steel fixing screws
- 3100K warm colour temperature: offering a pleasing light appearance
- · Push fit terminals



40m	<u>_</u>	_		80m

GENERAL INFORMATION			
Light Source	LED	Colour / Finish	Polished chrome effect
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	1.4 kg
Energy Efficiency Class	G		

TECHNICAL INFORMATION			
Nominal Voltage	240 V	Frequency	50Hz
Class Protection	1	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Metal
Construction Materials Line 2	Glass	Dimensions - Height	305 mm
Dimensions - Width	305 mm	Dimensions - Depth	80 mm

PRODUCT INFORMATION			
Wattage Combined	12W	CCT Combined	3100K
Luminaire Lumens Combined	800 lm	lm/W Combined	67 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP44		













PHOTOMETRICS					
Product Code	Product Type	Watts	сст	Luminaire lumens	Lm/W
PACIFIC12	Standard	12 W	3100 K	800 lm	67 lm/W

IP44	

PACKAGING		
Packaging Type	Colour Box	
Individual unit gross weight	1,681 g	
Pallet Layer Qty	35	
Pallet Layers	4	
Pallet Qty	140	
MOM / OPQ	1/5	





