



10W Polycarbonate LED Floodlight

10W Black Polycarbonate LED Floodlight

DESCRIPTION

High Lumen output, LED, floodlight with corrosion resistant polycarbonate body & quick fix bracket

FEATURES

- 10W, 800 Lumens, 25000 hours average rated life
- Pre-wired with 80cm cable
- Quick fix bracket allowing fixing without removing bracket from fixture
- Corrosion resistant polycarbonate body
- Various accessories available: HORBRACKET, POLYSPIKE and FLEDBPOLE

GENERAL INFORMATION

Light Source	LED	Colour / Finish	Black
Application	External	Mounting Type	Surface
Product Warranty	2 Years	Net Weight	0.44 kg
Energy Efficiency Class	G		

TECHNICAL INFORMATION

Nominal Voltage	230	Frequency	50Hz
Class Protection	2	Average Rated Life	25,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Polycarbonate
Construction Materials Line 2	Glass	Dimensions - Height	155 mm
Dimensions - Width	130 mm	Dimensions - Depth	50 mm
IP Rating	IP44		

PRODUCT INFORMATION

Wattage Combined	9W	CCT Combined	4000K
Luminaire Lumens Combined	800 lm	lm/W Combined	89 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
Lighting Technology used	LED	Non-Directional or Directional	NDLS



Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
CCT1/WATT1: Rated Peak Intensity	326 cd		



IP44





IP44

PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
POLY10	Standard	9 W	4000 K	800 lm	89 lm/W
POLY20PIR	PIR	19.9 W	4000 K	2000 lm	101 lm/W
POLY30	Standard	30 W	4000 K	3000 lm	100 lm/W

PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	564 g
Pallet Qty	0
MOM / OPQ	1 / 12

