



## 30W Polycarbonate LED Floodlight

30W Black Polycarbonate LED Floodlight

### DESCRIPTION

High Lumen output, LED, floodlight with corrosion resistant polycarbonate body & quick fix bracket

### FEATURES

- 30W, 3000 Lumens, 25000 hours average rated life
- Pre-wired with 80cm cable
- Quick fix bracket allowing fixing without removing bracket from fixture
- Corrosion resistant polycarbonate body
- Various accessories available: HORBRACKET, POLYSPIKE and FLEDBPOLE

### GENERAL INFORMATION

Light Source	LED	Colour / Finish	Black
Application	External	Mounting Type	Surface
Product Warranty	2 Years	Net Weight	0.97 kg
Energy Efficiency Class	G		

### TECHNICAL INFORMATION

Nominal Voltage	230	Frequency	50Hz
Class Protection	2	Average Rated Life	25,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Polycarbonate
Construction Materials Line 2	Glass	Dimensions - Height	195 mm
Dimensions - Width	170 mm	Dimensions - Depth	70 mm
IP Rating	IP44		

### PRODUCT INFORMATION

Wattage Combined	30W	CCT Combined	4000K
Luminaire Lumens Combined	3000 lm	lm/W Combined	100 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
Lighting Technology used	LED	Non-Directional or Directional	NDLS



Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
CCT1/WATT1: Rated Peak Intensity	1,300 cd		



IP44





PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
POLY10	Standard	9	4000 K	800 lm	89 lm/W
POLY20PIR	PIR	19.9	4000 K	2000 lm	101 lm/W
POLY30	Standard	30	4000 K	3000 lm	100 lm/W

PACKAGING	
Packaging Type	Colour Box
Individual unit gross weight	1,053 g
Pallet Layer Qty	72
Pallet Layers	4
Pallet Qty	288
MOM / OPQ	1 / 12

