



Photoelectric Switch With Timer

IP44 External Photoelectric Switch with Run Back Timer




DESCRIPTION

IP44 External Photoelectric Switch with Run Back Timer from 1-8 hours, able to control upto 250W of LED load

FEATURES

- Switching level adjustable between approx. 5-300 lux
- 10 Amp resistive, 3 Amp inductive load
- Run back timer adjustable to stay on between 1-8 hours after switch on
- Flexibility in operation for economic running costs
- Maximum 250W LED load capacity - 8 lights maximum



GENERAL INFORMATION

Colour / Finish	Grey	Application	External
Net Weight	0.19 kg		

TECHNICAL INFORMATION

Nominal Voltage	240	Construction Materials Line 1	ABS
Dimensions - Height	110 mm	Dimensions - Width	70 mm
Dimensions - Depth	38 mm	IP Rating	IP44

PRODUCT INFORMATION

Wattage Combined	250W
------------------	------



Product Code	Description	IP / IK Rating	Item Barcode
RDT10A	Photoelectric Switch With Timer	IP44	5013845008839



IP44

PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	167 g
Intermediate Carton Depth (mm)	83 mm
Intermediate Carton Width (mm)	265 mm
Intermediate Carton Height (mm)	123 mm
Intermediate Pack Qty.	5
Pallet Qty	0
MOM / OPQ	1 / 75

