



Carina



Carina chrome bulkhead 17W CCT selectable IP65 with step dim sensor

DESCRIPTION

Versatile range of decorative bulkheads, offering practicality and style with multiple functional options - perfect for superior leisure, hotels & outdoor applications

FEATURES

- Polycarbonate construction
- Full circular LED array
- IP65, ceiling or wall mounted
- Central BESA box mounting option on the base
- Colour temperature selectable 3100K, 4200K & 6400K
- Plug in connector between the terminal block and the gear tray. Terminal block is located on the base, allowing for easy wiring and the gear tray to be removed during installation
- 10% step dim microwave sensor
- Delay time to 10% operation adjustable: 5 sec / 30 sec / 1 min / 5 min / 15 min / 30 min
- detection range 100% / 75% / 50% / 25% / 10%



GENERAL INFORMATION

Light Source	LED	Colour / Finish	Polished chrome effect
Application	Internal/External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	1.31 kg
Energy Efficiency Class	E		

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	0 °C
Operating Temperature (Max)	45 °C	Average Rated Life	50,000 h
Number of switching cycles	25,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	325 mm	Dimensions - Width	325 mm
Dimensions - Depth	110 mm		

PRODUCT INFORMATION

Wattage Combined	17W	CCT Combined	3100K / 4200K / 6400K
Luminaire Lumens Combined	1480 - 1500 lm	lm/W Combined	87 - 88 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.8
IP Rating	IP65	IK Rating	IK08



PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
CSLEDCR	Standard, Chrome	17 W	3000 K	1480 lm	87 lm/W
			4200 K	1580 lm	93 lm/W
			6400 K	1500 lm	88 lm/W
CSLEDCREM3	Emergency, Chrome	17 W	3100 K	1480 lm	87 lm/W
			4200 K	1580 lm	93 lm/W
			6400 K	1500 lm	88 lm/W
CSLEDWH	Standard, White	17 W	3000 K	1480 lm	87 lm/W
			4200 K	1580 lm	93 lm/W
			6400 K	1500 lm	88 lm/W
CSLEDWHEM3	Emergency, White	17 W	3000 K	1480 lm	87 lm/W
			4200 K	1580 lm	93 lm/W
			6400 K	1500 lm	88 lm/W
MSCSLCREM3	Emergency, On / Off Microwave, Chrome	17 W	3100 K	1480 lm	87 lm/W
			4200 K	1580 lm	93 lm/W
			6400 K	1500 lm	88 lm/W
MSCSLEDCR	On / Off Microwave, Chrome	17 W	3100 K	1480 lm	87 lm/W
			4200 K	1580 lm	93 lm/W
			6400 K	1500 lm	88 lm/W
MSCSLEDWH	On / Off Microwave, White	17 W	3100 K	1480 lm	87 lm/W
			4200 K	1580 lm	93 lm/W
			6400 K	1500 lm	88 lm/W
MSCSLWHEM3	Emergency, On / Off Microwave, White	17 W	3100 K	1480 lm	87 lm/W
			4200 K	1580 lm	93 lm/W
			6400 K	1500 lm	88 lm/W
SDCSLCREM3	Emergency, Step Dim Microwave, Chrome	17 W	3100 K	1480 lm	87 lm/W
			4200 K	1580 lm	93 lm/W
			6400 K	1500 lm	88 lm/W
SDCSLEDCR	Step Dim Microwave, Chrome	17 W	3100 K	1480 lm	87 lm/W
			4200 K	1580 lm	93 lm/W
			6400 K	1500 lm	88 lm/W
SDCSLEDWH	Step Dim Microwave, White	17 W	3100 K	1480 lm	87 lm/W
			4200 K	1580 lm	93 lm/W
			6400 K	1500 lm	88 lm/W
SDCSLWHEM3	Emergency, Step Dim Microwave, White	17 W	3100 K	1480 lm	87 lm/W
			4200 K	1580 lm	93 lm/W
			6400 K	1500 lm	88 lm/W

ACCESSORIES		
Product Code	Description	MOM / OPQ
CFTCR	Chrome Trim for Carina Range	1 / 50

PACKAGING	
Packaging Type	Colour Box
Individual unit gross weight	1,229 g
Pallet Layer Qty	24
Pallet Layers	4
Pallet Qty	96
MOM / OPQ	1 / 8



IP65



IK08



Colour Temp. Selectable

