



## Carina



Carina white bulkhead 17W CCT selectable IP65 with step dim sensor and emergency

### DESCRIPTION

Versatile range of decorative bulkheads, offering practicality and style with multiple functional options - perfect for superior leisure, hotels & outdoor applications

### FEATURES

- Polycarbonate construction
- Full circular LED array
- IP65, ceiling or wall mounted
- Central BESA box mounting option on the base
- Colour temperature selectable 3100K, 4200K & 6400K
- Li-Ion 3.2V 1500mAh battery 5 year warranty - Replacement battery code: EB11
- Plug in connector between the terminal block and the gear tray. Terminal block is located on the base, allowing for easy wiring and the gear tray to be removed during installation
- 3 hour maintained mode as standard which can also be configured for non maintained operation
- 10% step dim microwave sensor
- Delay time to 10% operation adjustable: 5 sec / 30 sec / 1 min / 5 min / 15 min / 30 min



### GENERAL INFORMATION

|                  |                   |                         |         |
|------------------|-------------------|-------------------------|---------|
| Light Source     | LED               | Colour / Finish         | White   |
| Application      | Internal/External | Mounting Type           | Surface |
| Product Warranty | 5 Years           | Battery Warranty        | 5 Years |
| Net Weight       | 1.56 kg           | Energy Efficiency Class | E       |

### TECHNICAL INFORMATION

|                             |        |                               |               |
|-----------------------------|--------|-------------------------------|---------------|
| Nominal Voltage             | 240    | Frequency                     | 50Hz          |
| Class Protection            | 2      | Operating Temperature (Min)   | 0 °C          |
| Operating Temperature (Max) | 45 °C  | Average Rated Life            | 50,000 h      |
| Number of switching cycles  | 25,000 | Construction Materials Line 1 | Polycarbonate |
| Dimensions - Height         | 325 mm | Dimensions - Width            | 325 mm        |
| Dimensions - Depth          | 110 mm | IK Rating                     | IK08          |
| IP Rating                   | IP65   |                               |               |

### PRODUCT INFORMATION

|                           |                |                   |                       |
|---------------------------|----------------|-------------------|-----------------------|
| Wattage Combined          | 17W            | CCT Combined      | 3100K / 4200K / 6400K |
| Luminaire Lumens Combined | 1480 - 1500 lm | lm/W Combined     | 87 - 88 lm/w          |
| Beam Angle                | 120°           | CRI               | 80                    |
| SDCM                      | <6             | Lumen Maintenance | 0.8                   |



|                                  |        |                                  |              |
|----------------------------------|--------|----------------------------------|--------------|
| Emergency Lumen Output           | 193 lm | Dimmable                         | Not Dimmable |
| Displacement Factor              | 0.82   | CCT1/WATT1: Rated Peak Intensity | 355 cd       |
| CCT2/WATT1: Rated Peak Intensity | 396 cd | CCT3/WATT1: Rated Peak Intensity | 398 cd       |



IP65



IK08



Colour Temp.  
Selectable





IP65



IK08



Colour Temp.  
Selectable

## PHOTOMETRICS

| Product Code | Product Type                          | Watts | CCT    | Luminaire lumens | Lm/W    |
|--------------|---------------------------------------|-------|--------|------------------|---------|
| CSLEDCR      | Standard, Chrome                      | 14 W  | 3000 K | 1480 lm          |         |
|              |                                       |       | 4200 K | 1580 lm          |         |
|              |                                       |       | 6400 K | 1500 lm          |         |
| CSLEDCREM3   | Emergency, Chrome                     | 14 W  | 3000 K | 1480 lm          |         |
|              |                                       |       | 4200 K | 1580 lm          |         |
|              |                                       |       | 6400 K | 1500 lm          |         |
| CSLEDWH      | Standard, White                       | 14 W  | 3000 K | 1480 lm          |         |
|              |                                       |       | 4200 K | 1580 lm          |         |
|              |                                       |       | 6400 K | 1500 lm          |         |
| CSLEDWHEM3   | Emergency, White                      | 14 W  | 3000 K | 1480 lm          |         |
|              |                                       |       | 4200 K | 1580 lm          |         |
|              |                                       |       | 6400 K | 1500 lm          |         |
| MSCSLCREM3   | Emergency, On / Off Microwave, Chrome | 17 W  | 3100 K | 1480 lm          | 87 lm/W |
|              |                                       |       | 4200 K | 1580 lm          | 93 lm/W |
|              |                                       |       | 6400 K | 1500 lm          | 88 lm/W |
| MSCSLEDCR    | On / Off Microwave, Chrome            | 14 W  | 3000 K | 1480 lm          |         |
|              |                                       |       | 4200 K | 1580 lm          |         |
|              |                                       |       | 6400 K | 1500 lm          |         |
| MSCSLEDWH    | On / Off Microwave, White             | 14 W  | 3000 K | 1480 lm          |         |
|              |                                       |       | 4200 K | 1580 lm          |         |
|              |                                       |       | 6400 K | 1500 lm          |         |
| MSCSLWHEM3   | Emergency, On / Off Microwave, White  | 17 W  | 3100 K | 1480 lm          | 87 lm/W |
|              |                                       |       | 4200 K | 1580 lm          | 93 lm/W |
|              |                                       |       | 6400 K | 1500 lm          | 88 lm/W |
| SDCSLCREM3   | Emergency, Step Dim Microwave, Chrome | 17 W  | 3100 K | 1480 lm          | 87 lm/W |
|              |                                       |       | 4200 K | 1580 lm          | 93 lm/W |
|              |                                       |       | 6400 K | 1500 lm          | 88 lm/W |
| SDCSLEDCR    | Step Dim Microwave, Chrome            | 14 W  | 3000 K | 1480 lm          |         |
|              |                                       |       | 4200 K | 1580 lm          |         |
|              |                                       |       | 6400 K | 1500 lm          |         |
| SDCSLEDWH    | Step Dim Microwave, White             | 14 W  | 3000 K | 1480 lm          |         |
|              |                                       |       | 4200 K | 1580 lm          |         |
|              |                                       |       | 6400 K | 1500 lm          |         |
| SDCSLWHEM3   | Emergency, Step Dim Microwave, White  | 17 W  | 3100 K | 1480 lm          | 87 lm/W |
|              |                                       |       | 4200 K | 1580 lm          | 93 lm/W |
|              |                                       |       | 6400 K | 1500 lm          | 88 lm/W |

## ACCESSORIES

| Product Code | Description                       | MOM / OPQ |
|--------------|-----------------------------------|-----------|
| EB11         | Li-ion 3.2V 1500mAh Stick Battery | 1 / 1     |
| CFTCR        | Chrome Trim for Carina Range      | 1 / 50    |

## PACKAGING

|                              |            |
|------------------------------|------------|
| Packaging Type               | Colour Box |
| Individual unit gross weight | 1,317 g    |
| Pallet Layer Qty             | 24         |
| Pallet Layers                | 4          |



|            |       |
|------------|-------|
| Pallet Qty | 96    |
| MOM / OPQ  | 1 / 8 |



IP65



IK08



Colour Temp.  
Selectable

