



## SEEXITLI


Maintained or Non-Maintained Self Test Exit Box 4W LED 6000K with ISO 7010 up legend

### DESCRIPTION

Low energy compact alternative to standard emergency exit signs, robust steel construction with traditional battery test button for easy access, suitable to be adjusted for non-maintained operation to suit a number of commercial and industrial applications

### FEATURES

- Steel construction
- Push fit terminals
- 3 hour maintained mode as standard which can also be configured for non maintained operation
- Facility for remote switching
- Full range of interchangeable PC ISO 7010 legends available
- Diffuser on base
- Green LED charge light and emergency test button
- Red LED fault indicator
- Viewing distance 29m
- Battery - LiFePO4 3.2V 1000mAh



### GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Battery Warranty	5 Years
Net Weight	0.75 kg		

### TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	50,000 h
Number of switching cycles	25,000	Construction Materials Line 1	Steel
Construction Materials Line 2	PC	Dimensions - Height	180 mm
Dimensions - Width	300 mm	Dimensions - Depth	40 mm

### PRODUCT INFORMATION

Wattage Combined	4W	CCT Combined	6000K
Luminaire Lumens Combined	80 lm	lm/W Combined	20 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Emergency Lumen Output	80 lm
Lighting Technology used	LED	Dimmable	Not Dimmable



CCT1/WATT1: Rated Peak Intensity	75 cd		
----------------------------------	-------	--	--



## PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
VECOEXIT3M	Emergency	4 W	6200 K	70 lm	18 lm/W

## ACCESSORIES

Product Code	Description	MOM / OPQ
EB17	Li-Ion 3.2V 1500mAh Stick Battery	1 / 100
VECOISOD	Down Legend for Compact EM3 Exitbox	1 / 100
VECOISOL	Left Legend for Compact EM3 Exitbox	1 / 100
VECOISOR	Right Legend for Compact EM3 Exitbox	1 / 100

## PACKAGING

Packaging Type	Plain Box
Individual unit gross weight	0.75 g
Pallet Qty	0
MOM / OPQ	1 / 20

