



LED Batten


6ft 70W 4200K High Output LED Batten with Self Test Emergency

DESCRIPTION

6ft LED highly efficient traditional style batten fixture, slim profile design with even light distribution, front diffuser and end caps removable to allow for easy wiring at either end of the batten or Besa mounting from the rear of the fitting, available in both standard and high output mode to suit different ceiling heights and task requirements, comes complete with a bolt on self-test emergency downlight attached at the end of the fitting

FEATURES

- Full photometric data available to enable lighting designs. Light output is equivalent or superior to traditional fluorescent battens.
- Pressed steel body and polycarbonate diffuser. LED tray can be removed from the housing for easy installation
- BESA box mounting, gear tray retaining straps & push terminal connections
- 20mm knockout glands at each end for through wiring options
- Minimum 3 hour functionality in emergency mode
- 118 lumens in emergency mode
- >120 lm/W
- Replacement battery code: EB2



GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Battery Warranty	1 Year
Net Weight	2.42 kg		

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	35,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Steel
Construction Materials Line 2	Polycarbonate	Dimensions - Height	73 mm
Dimensions - Width	60 mm	Dimensions - Depth	1730 mm

PRODUCT INFORMATION

Wattage Combined	70W	CCT Combined	4200K
Luminaire Lumens Combined	8600 lm	lm/W Combined	123 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP20	Emergency Lumen Output	118 lm





PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
SELB4FTEM3	Emergency	23 W	4200 K	2930 lm	127 lm/W
SELB5FTEM3	Emergency	38 W	4200 K	4800 lm	126 lm/W
SELB5HOEM3	Emergency	65 W	4200 K	7900 lm	122 lm/W
SELB6FTEM3	Emergency	48 W	4200 K	6000 lm	125 lm/W
SELB6HOEM3	Emergency	70 W	4200 K	8600 lm	123 lm/W

ACCESSORIES		
Product Code	Description	MOM / OPQ
EB2	Ni-Cd 3.6V 2000mAh Stick Battery	1 / 1

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	2,637 g
Pallet Qty	0
MOM / OPQ	1 / 1

