



Self-Test LED Emergency Downlight


Self-Test recessed emergency downlight
1.4W LED 118lm with white and matt silver bezel

DESCRIPTION

Aluminium construction. Compact design. Pre-wired for easy installation

FEATURES

- Matt silver and white trims included
- LED glows green in standby mode and super bright white light in the event of a mains failure
- Excellent alternative to a converted downlight
- 118 lumens in emergency mode. 32mm diameter hole cut out size
- 3 hours duration in emergency mode
- Ni-Cd 3.6V 2000mAh battery 1 year warranty - Replacement battery code: EB2



GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Recessed
Product Warranty	5 Years	Battery Warranty	1 Year
Net Weight	0.36 kg		

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	1	Average Rated Life	30,000 h
Construction Materials Line 1	Aluminium	Dimensions - Height	45 mm
Dimensions - Width	45 mm	Dimensions - Depth	230 mm
IP Rating	IP20		

PRODUCT INFORMATION

Wattage Combined	1.4W	Luminaire Lumens Combined	118 lm
lm/W Combined	84 lm/w	Emergency Lumen Output	118 lm





PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
LDLEM3	Emergency	1.4 W	6000 K	120 lm	86 lm/W
SELDLEM3	Emergency, Self Test	1.4 W		118 lm	84 lm/W

ACCESSORIES		
Product Code	Description	MOM / OPQ
EB2	Ni-Cd 3.6V 2000mAh Stick Battery	1 / 1

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	368 g
Pallet Layer Qty	200
Pallet Layers	5
Pallet Qty	1,000
MOM / OPQ	1 / 20

