








Self-test maintained IP65 Emergency bulkhead 4W LED 6400K with ISO 7010 legend pack

DESCRIPTION

Rectangular functional Self test emergency bulkhead saving time and disruption to normal operation of the building. An energy efficient 4W solution offering 270 lumens in mains mode and 150 lumens in emergency mode. ISO7010 legend set provided with an option of signs directive available and a recessed frame to suit multiple applications

FEATURES

- Minimum 3 hour functionality in emergency mode. Facility for remote switching and non-maintained mode
- · Hinged gear tray & push fit terminal block: allows for quicker and easier installation and maintenance
- Central BESA box mounting option on the base
- · 20mm gland entries as standard
- Self-adhesive ISO 7010 legend pack included with a combination of symbols allowing multiple exit path designation options
- · Viewing distance 20m
- 270 lm when connected to mains, 150 lm when connected to battery



GENERAL INFORMATION			
Light Source	LED	Colourd Tinish code: EB19	White
Application	Internal/External	Mounting Type	Surface
Product Warranty	5 Years	Battery Warranty	5 Years
Net Weight	0.48 kg		

TECHNICAL INFORMATION			
Nominal Voltage	240 V	Frequency	50-60Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	40,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	110 mm	Dimensions - Width	355 mm
Dimensions - Depth	70 mm		

PRODUCT INFORMATION			
Wattage Combined	4W	CCT Combined	6400K
Luminaire Lumens Combined	130 lm	lm/W Combined	33 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.9
IP Rating	IP65	Emergency Lumen Output	152 lm
















l	P65

ACCESSORIES		
Product Code	Description	MOM / OPQ
EB19	Li-lon 3.2V 1500mAh Stick Battery	1 / 100
EB24	Li-lon 3.2V 1000mAh Stick Battery	1 / 10
BFRAME	Semi-Recessed Emergency Bulkhead Frame	1/50

PACKAGING		
Packaging Type	Plain Box	
Individual unit gross weight	563 g	
Pallet Layer Qty	60	
Pallet Layers	5	
Pallet Qty	300	
MOM / OPQ	1/10	







