



Self-Test Emergency Drop Sign

Self-Test emergency adjustable suspended white exit sign 2W LED 6000K with ISO 7010 up arrow

DESCRIPTION

Fitting with proven long term durability and performance – perfect for office & commercial applications

FEATURES

- Remote connection box complete with adjustable length suspension cable (max 80cm)
- Supplied with a double-sided exit legend
- 3 hour maintained mode as standard which can also be configured for non-maintained or remote switched operation
- Viewing distance 29m
- Ni-Cd 3.6V 800mAh battery 1 year warranty - Replacement battery code: EB8

GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Battery Warranty	1 Year
Net Weight	0.73 kg		

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	1	Average Rated Life	25,000 h
Construction Materials Line 1	Polycarbonate	Dimensions - Height	227 mm
Dimensions - Width	340 mm	Dimensions - Depth	45 mm
IP Rating	IP20		

PRODUCT INFORMATION

Wattage Combined	2.3W	CCT Combined	6000K
Luminaire Lumens Combined	170 lm	lm/W Combined	74 lm/w
Beam Angle	120°	Emergency Lumen Output	171 lm
Dimmable	Not Dimmable		





PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
SESIGNLEM3	Emergency	2.3	6000 K	170 lm	74 lm/W
SIGNLEDEM3	Emergency	3	6000 K	170 lm	57 lm/W

ACCESSORIES		
Product Code	Description	MOM / OPQ
EB8	Ni-Cd 3.6V 800mAh Side-by-side Battery	1 / 1
ISOSIGND	ISO Down Arrow Legend for SIGNLEDEM3 / SESIGNLEM3	1 / 100
ISOSIGNLR	ISO Left/Right Legend for SIGNLEDEM3 / SESIGNLEM3	1 / 100

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	769 g
Pallet Layer Qty	36
Pallet Layers	5
Pallet Qty	180
MOM / OPQ	1 / 6

