



## Self-Test Surface Mount EM3 Downlight



Self-Test white surface mount emergency downlight 3W LED 175lm

### DESCRIPTION

High quality, Self-Test emergency downlight, suitable for open area and corridor applications where solid ceilings exist

### FEATURES

- Polycarbonate construction & compact design
- Excellent solution where solid ceilings prevent recessed installation of an emergency downlight
- LED glows green in standby mode and super bright white light in the event of a mains failure
- Minimum 3 hour functionality in emergency mode. 175 lumens in emergency mode
- Supplied with open area lens. Corridor lens available separately - SESMDCL
- LiFePO4 3.2V 3000mAh battery 5 year warranty - Replacement battery code: EB38



### GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Battery Warranty	5 Years
Net Weight	0.43 kg		

### TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	1	Construction Materials Line 1	Plastic
Dimensions - Height	150 mm	Dimensions - Width	150 mm
Dimensions - Depth	45 mm	IP Rating	IP20

### PRODUCT INFORMATION

Wattage Combined	3W	CCT Combined	6000K
Luminaire Lumens Combined	175 lm	lm/W Combined	58 lm/w
Beam Angle	120°	Emergency Lumen Output	175 lm
Dimmable	Not Dimmable		





IP20

### PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
SESMDLEM3	Emergency, Self Test	3 W	6000 K	175 lm	58 lm/W

### ACCESSORIES

Product Code	Description	MOM / OPQ
EB15	Ni-Cd 3.6V 2Ah 3-Linked Battery	1 / 1
SESMDCL	Corridor Lens for SESMDLEM3	1 / 20

### PACKAGING

Packaging Type	Plain Box
Individual unit gross weight	437 g
Pallet Layer Qty	180
Pallet Layers	4
Pallet Qty	720
MOM / OPQ	1 / 20

