




IP20



IK08



Colour Temp.
Selectable



Self-Test Li-Ion Emergency LED Twinspot

Compact internal white twinspot 2 x 3W
200lm LED 6000K

DESCRIPTION

A flexible emergency light fitting which provides peace of mind thanks to long-lifetime, replaceable li-ion batteries, built-in automatic self-test functionality, durable product construction and long product warranty - perfect for commercial and industrial indoor applications

FEATURES

- Twin 4.5W individually rotatable LED projectors for widespread illumination in emergency operation
- Horizontally and vertically adjustable heads, with 180° rotation across the horizontal plane
- Individual indicator LEDs show 'healthy battery charge' or 'fault' status
- Replaceable long-life lithium-ion batteries; minimum 3 hour non-maintained functionality in emergency mode
- 3.2V Li-ion 4500mAh - Battery 1 year warranty - Replacement battery code: EB18
- Durable polycarbonate construction rated to IK08
- Push fit terminals

GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Battery Warranty	5 Years
Net Weight	0.8 kg		

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50-60Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	40,000 h
Number of switching cycles	25,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	284 mm	Dimensions - Width	250 mm
Dimensions - Depth	51 mm		

PRODUCT INFORMATION

Wattage Combined	4.5W	CCT Combined	6000K
Luminaire Lumens Combined	437 -	lm/W Combined	97 - 97 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP20	IK Rating	IK08



Emergency Lumen Output	437 lm
------------------------	--------





PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
VECOTWINSP	Emergency	2 W	6200 K	435 lm	218 lm/W
SETSPOT	Emergency	4.5 W	6000 K	437 lm	97 lm/W

ACCESSORIES		
Product Code	Description	MOM / OPQ
EB18	Li-Ion 3.2V 4500mAh Side-by-Side Battery	1 / 100

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	763 g
Pallet Layer Qty	120
Pallet Layers	2
Pallet Qty	240
MOM / OPQ	1 / 20

