




IP20



IK08



# Self-Test Li-Ion Emergency LED Twinspot

Compact internal white twinspot 2 x 3W  
200lm LED 6000K

### DESCRIPTION

A flexible emergency light fitting which provides peace of mind thanks to long-lifetime, replaceable li-ion batteries, built-in automatic self-test functionality, durable product construction and long product warranty – perfect for commercial and industrial indoor applications

### FEATURES

- Twin 4.5W individually rotatable LED projectors for widespread illumination in emergency operation
- Horizontally and vertically adjustable heads, with 180° rotation across the horizontal plane
- Individual indicator LEDs show ‘healthy battery charge’ or ‘fault’ status
- Replaceable long-life lithium-ion batteries; minimum 3 hour non-maintained functionality in emergency mode
- 3.2V Li-ion 4500mAh – Battery 1 year warranty – Replacement battery code: EB18
- Durable polycarbonate construction rated to IK08
- Push fit terminals

### GENERAL INFORMATION

|                  |          |                  |         |
|------------------|----------|------------------|---------|
| Light Source     | LED      | Colour / Finish  | White   |
| Application      | Internal | Mounting Type    | Surface |
| Product Warranty | 5 Years  | Battery Warranty | 5 Years |
| Net Weight       | 0.8 kg   |                  |         |

### TECHNICAL INFORMATION

|                             |        |                               |               |
|-----------------------------|--------|-------------------------------|---------------|
| Nominal Voltage             | 240 V  | Frequency                     | 50-60Hz       |
| Class Protection            | 2      | Operating Temperature (Min)   | -20 °C        |
| Operating Temperature (Max) | 45 °C  | Average Rated Life            | 40,000 h      |
| Number of switching cycles  | 25,000 | Construction Materials Line 1 | Polycarbonate |
| Dimensions – Height         | 284 mm | Dimensions – Width            | 250 mm        |
| Dimensions – Depth          | 51 mm  |                               |               |

### PRODUCT INFORMATION

|                           |       |                   |              |
|---------------------------|-------|-------------------|--------------|
| Wattage Combined          | 4.5W  | CCT Combined      | 6000K        |
| Luminaire Lumens Combined | 437 - | lm/W Combined     | 97 - 97 lm/w |
| Beam Angle                | 120°  | CRI               | 80           |
| SDCM                      | <6    | Lumen Maintenance | 0.7          |
| IP Rating                 | IP20  | IK Rating         | IK08         |



| PHOTOMETRICS |              |       |        |                  |          |
|--------------|--------------|-------|--------|------------------|----------|
| Product Code | Product Type | Watts | CCT    | Luminaire lumens | Lm/W     |
| VECOTWINSP   | Emergency    | 2 W   | 6200 K | 435 lm           | 218 lm/W |
| SETSPOT      | Emergency    | 4.5 W | 6000 K | 437 lm           | 97 lm/W  |

| ACCESSORIES  |  |           |
|--------------|--|-----------|
| Product Code | Description                              | MOM / OPQ |
| EB18         | Li-Ion 3.2V 4500mAh Side-by-Side Battery | 1 / 100   |

| PACKAGING                    |           |
|------------------------------|-----------|
| Packaging Type               | Plain Box |
| Individual unit gross weight | 763 g     |
| Pallet Qty                   | 0         |
| MOM / OPQ                    | 1 / 20    |