Spec Sheet SFLWW15







LED Super Flat Strip Lights

550mm 3W Super Flat Strip LED 3000K


DESCRIPTION

Ultra low power consumption with excellent light output. The inclusion of a link lead and butt connector allows continuous linear, spaced linear or radial installations

FEATURES

- Ultra-bright warm white LEDs for a pleasing lighting effect
- · Reeded diffuser for soft diffused light
- Fixing clips included for under-cabinet or wall installation
- 300mm link lead and butt connector included allowing flexible linking options





GENERAL INFORMATION			
Light Source	LED	Colour / Finish	Matt silver effect
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.09 kg
Energy Efficiency Class	F		

TECHNICAL INFORMATION			
Nominal Voltage	240 V	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	0 °C
Operating Temperature (Max)	45 °C	Average Rated Life	20,000 h
Number of switching cycles	10,000	Construction Materials Line 1	Aluminium
Construction Materials Line 2	PC	Dimensions - Height	550 mm
Dimensions - Width	18 mm	Dimensions - Depth	9 mm

PRODUCT INFORMATION			
Wattage Combined	3W	CCT Combined	3000K
Luminaire Lumens Combined	360 lm	Im/W Combined	120 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP20		













PHOTOMETRICS					
Product Code	Product Type	Watts	сст	Luminaire lumens	Lm/W
SFLWW15	Standard	3 W	3000 K	360 lm	120 lm/W
SFLWW9	Standard	1.8 W	3000 K	230 lm	128 lm/W

IP20	

PACKAGING		
Packaging Type	Colour Box	
Individual unit gross weight	109 g	
Intermediate Carton Depth (mm)	60 mm	
Intermediate Carton Width (mm)	560 mm	
Intermediate Carton Height (mm)	120 mm	
Intermediate Pack Qty.	10	
Pallet Layer Qty	600	
Pallet Layers	4	
Pallet Qty	2,400	
MOM / OPQ	1 / 100	

CE





