





LED Super Flat Strip Lights 350mm 1.8W Super Flat LED Strip 3000K

DESCRIPTION

Ultra low power consumption with excellent light output. The inclusion of a link lead and butt connector allows continuous linear, spaced linear or radial installations

FEATURES

- Ultra-bright warm white LEDs for a pleasing lighting effect
- Reeded diffuser for soft diffused light
- Fixing clips included for under-cabinet or wall installation
- 300mm link lead and butt connector included allowing flexible linking options



Driver	M M M
140mm 4	5mm
0 0 0 0 0 0 0 0	
350 / 550mm	18.6mm

GENERAL INFORMATION			
Light Source	LED	Colour / Finish	Matt silver effect
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.06 kg
Energy Efficiency Class	F		

TECHNICAL INFORMATION			
Nominal Voltage	240 V	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	0 °C
Operating Temperature (Max)	45 °C	Average Rated Life	20,000 h
Number of switching cycles	10,000	Construction Materials Line 1	Aluminium
Construction Materials Line 2	PC	Dimensions - Height	350 mm
Dimensions - Width	18 mm	Dimensions - Depth	9 mm

PRODUCT INFORMATION			
Wattage Combined	1.8W	CCT Combined	3000K
Luminaire Lumens Combined	230 lm	lm/W Combined	128 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP20		













PHOTOMETRICS					
Product Code	Product Type	Watts	ССТ	Luminaire lumens	Lm/W
SFLWW15	Standard	3 W	3000 K	360 lm	120 lm/W
SFLWW9	Standard	1.8 W	3000 K	230 lm	128 lm/W



PACKAGING		
Packaging Type	Colour Box	
Individual unit gross weight	84 g	
Intermediate Carton Depth (mm)	60 mm	
Intermediate Carton Width (mm)	360 mm	
Intermediate Carton Height (mm)	120 mm	
Intermediate Pack Qty.	10	
Pallet Layer Qty	1,000	
Pallet Layers	4	
Pallet Qty	4,000	
MOM / OPQ	1 / 100	

CE





