



LED Emergency Exit Drop Sign

LED Emergency Hanging Exit Sign Light

DESCRIPTION

Fitting with proven long term durability and performance – perfect for office & commercial applications

FEATURES

- Remote connection box complete with adjustable length suspension cable (max 80cm)
- Supplied with a double-sided exit legend
- 3 hour maintained mode as standard which can also be configured for non-maintained or remote switched operation
- Viewing distance 29m
- Battery – Ni-Cd 3.6V 800mAh. Battery 1 year warranty – Replacement battery code: EB8
- Test button and LED charge light

GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Suspended
Product Warranty	5 Years	Battery Warranty	1 Year
Net Weight	0.75 kg		

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	0 °C
Operating Temperature (Max)	40 °C	Average Rated Life	25,000 h
Construction Materials Line 1	Polycarbonate	Construction Materials Line 2	Acrylic Panel
Dimensions – Height	227 mm	Dimensions – Width	340 mm
Dimensions – Depth	45 mm		

PRODUCT INFORMATION

Wattage Combined	3W	CCT Combined	6000K
Luminaire Lumens Combined	170 lm	lm/W Combined	57 lm/w
IP Rating	IP20		





IP20

PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
SESIGNLEM3	Emergency	2.3 W	6000 K	170 lm	74 lm/W
SIGNLEDEM3	Emergency	3 W	6000 K	170 lm	57 lm/W

ACCESSORIES

Product Code	Description	MOM / OPQ
EB8	Ni-Cd 3.6V 800mAh Side-by-side Battery	1 / 1
ISOSIGND	ISO Down Arrow Legend for SIGNLEDEM3 / SESIGNLEM3	1 / 100
ISOSIGNLR	ISO Left/Right Legend for SIGNLEDEM3 / SESIGNLEM3	1 / 100
SIGNLGD	Left/Right Legend for SIGNLEDEM3	1 / 100
SIGNLGDUP	Up Arrow Legend for SIGNLEDEM3	1 / 100

PACKAGING

Packaging Type	Plain Box
Individual unit gross weight	754 g
Pallet Layer Qty	36
Pallet Layers	4
Pallet Qty	144
MOM / OPQ	1 / 6

