



## SLICE


Slim low level black surface fitting 3W LED  
4000K 188lm IP65

### DESCRIPTION

Superslim surface mounting mains voltage LED amenity fixtures for garden and path illumination which offer a fantastic alternative to traditional bricklights without the hassle of recessed installation.

### FEATURES

- White trim available - TRIMLONG



### GENERAL INFORMATION

Light Source	LED	Colour / Finish	Black
Application	External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.22 kg
Energy Efficiency Class	D		

### TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	20,000 h
Number of switching cycles	10,000	Construction Materials Line 1	ABS
Construction Materials Line 2	PC	Dimensions - Height	178 mm
Dimensions - Width	38 mm	Dimensions - Depth	17 mm
IP Rating	IP65		

### PRODUCT INFORMATION

Wattage Combined	3W	CCT Combined	4000K
Luminaire Lumens Combined	330 lm	lm/W Combined	110 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7





IP65

Lighting Technology used	LED	Non-Directional or Directional	NDLS
Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Correlated Colour temperature type	SINGLE_VALUE
Chromaticity coordinates x	0.376	Chromaticity coordinates y	0.385
Stroboscopic effect metric (SVM)	0.0	Flicker Metric (pst)	0.1
R9 colour rendering index	1.0	Survival factor @6000hrs	1.0
Claim LED Replace Fluorescent	FALSE	Spectrum report available	Yes
Displacement Factor	0.5		





IP65

### PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
SLICELONG	Standard	3 W	4000 K	330 lm	110 lm/W

### ACCESSORIES

Product Code	Description	MOM / OPQ
TRIMLONG	White Trim for SLICELONG	1 / 40

### PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	251 g
Pallet Layer Qty	336
Pallet Layers	3
Pallet Qty	1,008
MOM / OPQ	1 / 24

