Spec Sheet SPOTLEDWAL









Aluminium LED Wall Spot Light


Aluminium Wall Spot Light 4W LED 4000K **IP44 Satin Nickel**

DESCRIPTION

Aluminium LED wall spot light in satin nickel finish with a frosted glass lens is a simple option for up or downlighting. Additionally the LED lamp head is fully adjustable to direct the light where needed

FEATURES

- Aluminium construction & frosted glass lens
- Integrated driver and LED light source
- · Fully adjustable head



GENERAL INFORMATION			
Light Source	LED	Colour / Finish	Brushed nickel effect
Application	External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.35 kg
Energy Efficiency Class	G		

TECHNICAL INFORMATION			
Nominal Voltage	240 V	Frequency	50Hz
Class Protection	1	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Aluminium
Dimensions - Height	100 mm	Dimensions - Width	60 mm
Dimensions - Depth	130 mm		

PRODUCT INFORMATION			
Wattage Combined	4W	CCT Combined	4000K
Luminaire Lumens Combined	240 lm	lm/W Combined	60 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP44		













PHOTOMETRICS					
Product Code	Product Type	Watts	сст	Luminaire lumens	Lm/W
SPOTLEDGAR	Standard	4.3 W	4000 K	240 lm	56 lm/W
SPOTLEDWAL	Standard	4 W	4000 K	240 lm	60 lm/W

ID // /	

PACKAGING		
Packaging Type	Colour Box	
Individual unit gross weight	402 g	
Pallet Layer Qty	192	
Pallet Layers	3	
Pallet Qty	576	
MOM / OPQ	1/12	





