

### Spec Sheet SQOPALMW3







## **Fresh Prince**

Fresh Prince square opal diffuser LED bulkhead 18W 4000K IP65 with integral microwave sensor and emergency

eterna.

#### DESCRIPTION

High output, energy saving utility LED wall / ceiling fixtures with standard, emergency & multi-function microwave control versions. Both opal & clear versions are available for either smooth diffused effect or maximum light output. Diffusers are supplied not fitted to bases and fully captive diffuser fixing screws are utilised to save installation time. Multi-function microwave versions provide the best in flexibility & energy saving options.

#### FEATURES

- Full circular / square LED array
- Push fit terminals, hinged gear tray & captive fixing screws
- · Four 20mm cable entries on the side and one to the rear
- Central BESA box mounting option on the base
- 3 hour maintained mode as standard which can also be configured for non maintained operation
- Li-Ion 3.2V 1500mAh battery 5 year warranty Replacement battery code: EB11
- Detection sensitivity adjustable 10/50/75/100%
- Daylight sensor adjustable 5/15/50 Lux/Disable
- Mounting height maximum 6m
- Detection angle 150° wall mounted, 360° ceiling mounted

	GENERA	AL INFORMATION					
Light Source	LED	Colour / Finish	White				
Application	Internal/External	Mounting Type	Surface				
Product Warranty	5 Years	Battery Warranty	5 Years				
Net Weight	1.36 kg	Energy Efficiency Class	E				
TECHNICAL INFORMATION							
Nominal Voltage	240 V	Frequency	50Hz				
Class Protection	1	Operating Temperature (Min)	-20 °C				
Operating Temperature (Max)	45 °C	Average Rated Life	50,000 h				
Number of switching cycles	25,000	<b>Construction Materials Line 1</b>	Polycarbonate				
Dimensions - Height	250 mm	Dimensions - Width	250 mm				
Dimensions - Depth	100 mm						
	PRODUC	CT INFORMATION					
Wattage Combined	18W	CCT Combined	4000K				
Luminaire Lumens Combined	1610 lm	Im/W Combined	89 lm/w				
Beam Angle	120°	CRI	80				
SDCM	<6	Lumen Maintenance	0.8				
IP Rating	IP65	IK Rating	IK08				





Registered In England No. 410716 VAT Reg. No. GB 229 3783 37 Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

Member of 🕖

CE

# eterna.

PHOTOMETRICS							
Product Code	Product Type	Watts	ССТ	Luminaire lumens	Lm/W		
CIROPALEM3	Emergency	18 W	4000 K	1400 lm	78 lm/W		
CIROPALSTD	Standard, Circular Opal	18 W	4000 K	1400 lm	78 lm/W		
CIRPRISEM3	Emergency, Circular Prismatic	18 W	4000 K	1400 lm	78 lm/W		
CIRPRISMW	On / Off Microwave, Circular Prismatic	18 W	4000 K	1400 lm	78 lm/W		
CIRPRISMW3	Emergency, On / Off Microwave, Circular Prismatic	18 W	4000 K	1400 lm	78 lm/W		
SQOPALMW	On / Off Microwave	18 W	4000 K	1610 lm	89 lm/W		
SQOPALMW3	Emergency, On / Off Microwave	18 W	4000 K	1610 lm	89 lm/W		
SQOPALSTD	Standard	18 W	4000 K	1610 lm	89 lm/W		
SQPRISMW	On / Off Microwave	18 W	4000 K	1720 lm	96 lm/W		

ACCESSORIES				
Product Code	Description	мом / орд		
EB11	Li-ion 3.2V 1500mAh Stick Battery	1/1		

PACKAGING				
Packaging Type	Colour Box			
Individual unit gross weight	1,302 g			
Pallet Qty	0			
мом / орд	1/8			







Registered In England No. 410716 VAT Reg. No. GB 229 3783 37 Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D



IP65

IK08