



## Fresh Prince



Fresh Prince square opal diffuser LED bulkhead 18W 4000K IP65 with integral microwave sensor and emergency

### DESCRIPTION

High output, energy saving utility LED wall / ceiling fixtures with standard, emergency & multi-function microwave control versions. Both opal & clear versions are available for either smooth diffused effect or maximum light output. Diffusers are supplied not fitted to bases and fully captive diffuser fixing screws are utilised to save installation time. Multi-function microwave versions provide the best in flexibility & energy saving options.

### FEATURES

- Full circular / square LED array
- Push fit terminals, hinged gear tray & captive fixing screws
- Four 20mm cable entries on the side and one to the rear
- Central BESA box mounting option on the base
- 3 hour maintained mode as standard which can also be configured for non maintained operation
- Li-Ion 3.2V 1500mAh battery 5 year warranty - Replacement battery code: EB11
- Detection sensitivity adjustable 10/50/75/100%
- Daylight sensor adjustable - 5/15/50 Lux/Disable



### GENERAL INFORMATION

<b>Light Source</b>	LED	<b>Colour / Finish</b>	White
<b>Application</b>	Internal/External	<b>Mounting Type</b>	Surface
<b>Product Warranty</b>	5 Years	<b>Battery Warranty</b>	5 Years
<b>Net Weight</b>	1.36 kg	<b>Energy Efficiency Class</b>	E

### TECHNICAL INFORMATION

<b>Nominal Voltage</b>	240	<b>Frequency</b>	50Hz
<b>Class Protection</b>	1	<b>Operating Temperature (Min)</b>	-20 °C
<b>Operating Temperature (Max)</b>	45 °C	<b>Average Rated Life</b>	50,000 h
<b>Number of switching cycles</b>	25,000	<b>Construction Materials Line 1</b>	Polycarbonate
<b>Dimensions - Height</b>	250 mm	<b>Dimensions - Width</b>	250 mm
<b>Dimensions - Depth</b>	100 mm	<b>IK Rating</b>	IK08
<b>IP Rating</b>	IP65		

### PRODUCT INFORMATION

<b>Wattage Combined</b>	18W	<b>CCT Combined</b>	4000K
<b>Luminaire Lumens Combined</b>	1610 lm	<b>lm/W Combined</b>	89 lm/w
<b>Beam Angle</b>	120°	<b>CRI</b>	80
<b>SDCM</b>	<6	<b>Lumen Maintenance</b>	0.8



Emergency Lumen Output	193 lm	Lighting Technology used	LED
Non-Directional or Directional	NDLS	Mains or non-mains	MLS
Connected light source (CLS)	FALSE	Colour tuneable light source	FALSE
High Luminance light source	FALSE	Anti Glare shield	FALSE
Correlated Colour temperature type	SINGLE_VALUE	Correlated Colour temperature (K) 1	4,000
Chromaticity coordinates x	0.369	Chromaticity coordinates y	0.372
Peak Luminous Intensity (cd)	398 cd	Stroboscopic effect metric (SVM)	0.0
Flicker Metric (pst)	0.0	R9 colour rendering index	7.0
Survival factor @6000hrs	0.9	Claim LED Replace Fluorescent	FALSE
Spectrum report available	Yes	Displacement Factor	0.91
CCT1/WATT1: Rated Peak Intensity	398 cd		





IP65



IK08

## PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
CIROPALEM3	Emergency	18	4000 K	1400 lm	78 lm/W
CIROPALSTD	Standard, Circular Opal	18	4000 K	1400 lm	78 lm/W
CIRPRISEM3	Emergency, Circular Prismatic	18	4000 K	1400 lm	78 lm/W
CIRPRISMW	On / Off Microwave, Circular Prismatic	18	4000 K	1400 lm	78 lm/W
CIRPRISMW3	Emergency, On / Off Microwave, Circular Prismatic	18	4000 K	1400 lm	78 lm/W
SQOPALMW	On / Off Microwave	18	4000 K	1610 lm	89 lm/W
SQOPALMW3	Emergency, On / Off Microwave	18	4000 K	1610 lm	89 lm/W
SQOPALSTD	Standard	18	4000 K	1610 lm	89 lm/W
SQPRISMW	On / Off Microwave	18	4000 K	1720 lm	96 lm/W

## ACCESSORIES

Product Code	Description	MOM / OPQ
EB11	Li-ion 3.2V 1500mAh Stick Battery	1 / 1

## PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	1,302 g
Pallet Layer Qty	64
Pallet Layers	2
Pallet Qty	128
MOM / OPQ	1 / 8

