
Spec Sheet SSARCDWH









Single Fused A Rated RCD Spur

Single Unswitched White A Rated RCD Socket

DESCRIPTION

Single unswitched white type A rated RCD socket to ensure tripping for residual AC and pulsating DC currents. Simple to install, fused RCD spur, perfect for electrical protection of permanently installed products such as refrigeration units and hand dryers

FEATURES

- Highly stable and reliable polycarbonate construction, with raised square profile and screwed faceplate
- Type A rated to ensure tripping for residual a.c. currents and pulsating d.c. currents
- 13A fused spur with "passive" 30mA RCD protection at less than 40ms (typical)
- · Complete with TEST button
- · Twin earth terminals for easy cable connections
- Mechanical latching (no need to reset after power loss)

GENERAL INFORMATION				
Colour / Finish	White	Application	Internal	
Product Warranty	1 Year	Net Weight	0.19 kg	

TECHNICAL INFORMATION				
Construction Materials Line 1	Polycarbonate	Dimensions - Height	86 mm	
Dimensions - Width	86 mm	Dimensions - Depth	38 mm	













Product Code	Description	Item Barcode
SSARCDWH	Single Fused A Rated RCD Spur	5013845000123

PACKAGING			
Packaging Type	Colour Box		
Individual unit gross weight	46.8 g		
Intermediate Carton Depth (mm)	170 mm		
Intermediate Carton Width (mm)	115 mm		
Intermediate Carton Height (mm)	100 mm		
Intermediate Pack Qty.	5		
Pallet Qty	0		
MOM / OPQ	1/60		





