



Single Fused A Rated RCD  
Spur


Single Unswitched White A Rated RCD Socket

DESCRIPTION

Single unswitched white type A rated RCD socket to ensure tripping for residual AC and pulsating DC currents. Simple to install, fused RCD spur, perfect for electrical protection of permanently installed products such as refrigeration units and hand dryers

FEATURES

- Highly stable and reliable polycarbonate construction, with raised square profile and screwed faceplate
- Type A rated to ensure tripping for residual a.c. currents and pulsating d.c. currents
- 13A fused spur with “passive” 30mA RCD protection at less than 40ms (typical)
- Complete with TEST button
- Twin earth terminals for easy cable connections
- Mechanical latching (no need to reset after power loss)



GENERAL INFORMATION

Colour / Finish	White	Application	Internal
Product Warranty	1 Year	Net Weight	0.19 kg

TECHNICAL INFORMATION

Construction Materials Line 1	Polycarbonate	Dimensions - Height	86 mm
Dimensions - Width	86 mm	Dimensions - Depth	38 mm



Product Code	Description	Item Barcode
SSARCDWH	Single Fused A Rated RCD Spur	5013845000123

PACKAGING	
Packaging Type	Colour Box
Individual unit gross weight	46.8 g
Intermediate Carton Depth (mm)	170 mm
Intermediate Carton Width (mm)	115 mm
Intermediate Carton Height (mm)	100 mm
Intermediate Pack Qty.	5
Pallet Qty	0
MOM / OPQ	1 / 60

