



Single Fused A Rated RCD Spur

Single Unswitched White A Rated RCD Socket

DESCRIPTION

Single unswitched white type A rated RCD socket to ensure tripping for residual AC and pulsating DC currents. Simple to install, fused RCD spur, perfect for electrical protection of permanently installed products such as refrigeration units and hand dryers

FEATURES

- Highly stable and reliable polycarbonate construction, with raised square profile and screwed faceplate
- Type A rated to ensure tripping for residual a.c. currents and pulsating d.c. currents
- 13A fused spur with "passive" 30mA RCD protection at less than 40ms (typical)
- Complete with TEST button
- Twin earth terminals for easy cable connections
- Mechanical latching (no need to reset after power loss)

GENERAL INFORMATION

| | | | |
|------------------|--------|-------------|----------|
| Colour / Finish | White | Application | Internal |
| Product Warranty | 1 Year | Net Weight | 0.19 kg |

TECHNICAL INFORMATION

| | | | |
|-------------------------------|---------------|---------------------|-------|
| Construction Materials Line 1 | Polycarbonate | Dimensions - Height | 86 mm |
| Dimensions - Width | 86 mm | Dimensions - Depth | 38 mm |



| Product Code | Description | Item Barcode |
|--------------|-------------------------------|---------------|
| SSARCDWH | Single Fused A Rated RCD Spur | 5013845000123 |

PACKAGING

| | |
|---------------------------------|------------|
| Packaging Type | Colour Box |
| Individual unit gross weight | 46.8 g |
| Intermediate Carton Depth (mm) | 170 mm |
| Intermediate Carton Width (mm) | 115 mm |
| Intermediate Carton Height (mm) | 100 mm |
| Intermediate Pack Qty. | 5 |
| Pallet Layer Qty | 240 |
| Pallet Layers | 8 |
| Pallet Qty | 1,920 |
| MOM / OPQ | 1 / 60 |

CE

UK
CA