



## 10W Tablet LED Floodlight


10W Black Tablet LED Floodlight

### DESCRIPTION

Super slim, aesthetically pleasing LED floodlight with black & white, PIR and non PIR available.

### FEATURES

- Mains voltage LED chips - no driver required
- Quick fix bracket allowing fixing without removing bracket from fixture
- Pre-wired with 80cm black flex



### GENERAL INFORMATION

|                         |          |                 |         |
|-------------------------|----------|-----------------|---------|
| Light Source            | LED      | Colour / Finish | Black   |
| Application             | External | Mounting Type   | Surface |
| Product Warranty        | 2 Years  | Net Weight      | 0.29 kg |
| Energy Efficiency Class | G        |                 |         |

### TECHNICAL INFORMATION

|                               |        |                               |           |
|-------------------------------|--------|-------------------------------|-----------|
| Nominal Voltage               | 240    | Frequency                     | 50Hz      |
| Class Protection              | 1      | Average Rated Life            | 30,000 h  |
| Number of switching cycles    | 15,000 | Construction Materials Line 1 | Aluminium |
| Construction Materials Line 2 | PC     | Dimensions - Height           | 95 mm     |
| Dimensions - Width            | 125 mm | Dimensions - Depth            | 25 mm     |
| IP Rating                     | IP65   |                               |           |

### PRODUCT INFORMATION

|                                |        |                          |         |
|--------------------------------|--------|--------------------------|---------|
| Wattage Combined               | 10W    | CCT Combined             | 4000K   |
| Luminaire Lumens Combined      | 750 lm | lm/W Combined            | 75 lm/w |
| Beam Angle                     | 120°   | CRI                      | 80      |
| SDCM                           | <6     | Lighting Technology used | LED     |
| Non-Directional or Directional | NDLS   | Mains or non-mains       | MLS     |



|                              |              |                                  |        |
|------------------------------|--------------|----------------------------------|--------|
| Connected light source (CLS) | FALSE        | Colour tuneable light source     | FALSE  |
| High Luminance light source  | FALSE        | Anti Glare shield                | FALSE  |
| Dimmable                     | Not Dimmable | CCTI/WATTI: Rated Peak Intensity | 231 cd |



IP65





| PHOTOMETRICS |              |       |        |                  |         |
|--------------|--------------|-------|--------|------------------|---------|
| Product Code | Product Type | Watts | CCT    | Luminaire lumens | Lm/W    |
| TAB10BK      | Standard     | 10 W  | 4000 K | 750 lm           | 75 lm/W |
| TAB10WH      | Standard     | 10 W  | 4000 K | 750 lm           | 75 lm/W |
| TAB20BK      | Standard     | 20 W  | 4000 K | 1500 lm          | 75 lm/W |
| TAB20WH      | Standard     | 20 W  | 4000 K | 1500 lm          | 75 lm/W |

| PACKAGING                    |            |
|------------------------------|------------|
| Packaging Type               | Colour Box |
| Individual unit gross weight | 425 g      |
| Pallet Qty                   | 0          |
| MOM / OPQ                    | 1 / 40     |

