



## 10W Tablet LED Floodlight

10W White Tablet LED Floodlight

### DESCRIPTION

Super slim, aesthetically pleasing LED floodlight with black & white, PIR and non PIR available.

### FEATURES

- Mains voltage LED chips - no driver required
- Quick fix bracket allowing fixing without removing bracket from fixture
- Pre-wired with 80cm black flex

### GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	External	Mounting Type	Surface
Product Warranty	2 Years	Net Weight	0.29 kg
Energy Efficiency Class	G		

### TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	1	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Aluminium
Construction Materials Line 2	PC	Dimensions - Height	95 mm
Dimensions - Width	125 mm	Dimensions - Depth	25 mm
IP Rating	IP65		

### PRODUCT INFORMATION

Wattage Combined	10W	CCT Combined	4000K
Luminaire Lumens Combined	750 lm	lm/W Combined	75 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lighting Technology used	LED
Non-Directional or Directional	NDLS	Mains or non-mains	MLS



Connected light source (CLS)	FALSE	Colour tuneable light source	FALSE
High Luminance light source	FALSE	Anti Glare shield	FALSE
Dimmable	Not Dimmable	CCTI/WATTI: Rated Peak Intensity	231 cd



IP65





PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
TAB10BK	Standard	10 W	4000 K	750 lm	75 lm/W
TAB10WH	Standard	10 W	4000 K	750 lm	75 lm/W
TAB20BK	Standard	20 W	4000 K	1500 lm	75 lm/W
TAB20WH	Standard	20 W	4000 K	1500 lm	75 lm/W

PACKAGING	
Packaging Type	Colour Box
Individual unit gross weight	427 g
Pallet Qty	0
MOM / OPQ	1 / 40

