



IP66 Rated Time Delay Switch


IP66 16Amp Electronic Outdoor Time Delay Switch

DESCRIPTION

The outdoor time delay switch is an ideal solution for a number of applications including lighting and heating. Different delay functions from 2 seconds to 2 hours firstly allows for energy saving and also flexibility to suit hospitality and utility applications

FEATURES

- Multi range delay function from 2 seconds to 2 hours - reduces energy consumption
- Incandescent 16 Amp max, fluorescent 6 Amp max, compact fluorescent 3 Amp max (maximum six fluorescent lights), low voltage 3 Amp max & fans and ventilation equipment 3 Amp max
- Multiple accurate time settings using DIP switches and rotary adjuster
- Multi point switching, connect two or more units in parallel



GENERAL INFORMATION

Colour / Finish	Grey	Application	External
Product Warranty	1 Year	Net Weight	0.10 kg

TECHNICAL INFORMATION

Nominal Voltage	240	Construction Materials Line 1	ABS
Dimensions - Height	110 mm	Dimensions - Width	80 mm
Dimensions - Depth	70 mm	IP Rating	IP66





IP66

Product Code	Description	IP / IK Rating	Item Barcode
TLS68EX	IP66 Rated Time Delay Switch	IP66	5013845028912

PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	260 g
Intermediate Carton Depth (mm)	245 mm
Intermediate Carton Width (mm)	390 mm
Intermediate Carton Height (mm)	95 mm
Intermediate Pack Qty.	5
Pallet Layer Qty	250
Pallet Layers	2
Pallet Qty	500
MOM / OPQ	1 / 50

