
Spec Sheet TLS68EX





IP66 Rated Time Delay Switch

IP66 16Amp Electronic Outdoor Time Delay Switch

DESCRIPTION

The outdoor time delay switch is an ideal solution for a number of applications including lighting and heating. Different delay functions from 2 seconds to 2 hours firstly allows for energy saving and also flexibility to suit hospitality and utility applications

FEATURES

- Multi range delay function from 2 seconds to 2 hours - reduces energy consumption
- Incandescent 16 Amp max, fluorescent 6 Amp max, compact fluorescent 3 Amp max (maximum six fluorescent lights), low voltage 3 Amp max & fans and ventilation equipment 3 Amp max
- Multiple accurate time settings using DIP switches and rotary adjuster
- Multi point switching, connect two or more units in parallel

GENERAL INFORMATION			
Colour / Finish	Grey	**Application**	External
Product Warranty	1 Year	**Net Weight**	0.10 kg

TECHNICAL INFORMATION			
Nominal Voltage	240	**Construction Materials Line 1**	ABS
Dimensions - Height	110 mm	**Dimensions - Width**	80 mm
Dimensions - Depth	70 mm	**IP Rating**	IP66

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

Product Code	Description	IP / IK Rating	Item Barcode
TLS68EX	IP66 Rated Time Delay Switch	IP66	5013845028912

PACKAGING	
Packaging Type	Colour Box
Individual unit gross weight	260 g
Intermediate Carton Depth (mm)	245 mm
Intermediate Carton Width (mm)	390 mm
Intermediate Carton Height (mm)	95 mm
Intermediate Pack Qty.	5
Pallet Layer Qty	250
Pallet Layers	2
Pallet Qty	500
MOM / OPQ	1 / 50