



Twin Unswitched Metal Clad A Rated RCD Socket

Twin Unswitched Metal Clad A Rated RCD Socket

DESCRIPTION

Simple to install 2-gang unswitched passive RCD socket with durable metal clad exterior, perfect for providing local electrical protection in garages, workshops or warehouses

FEATURES

- Pressed steel construction with screwed faceplate. Easy cable-entry via knock-outs available on the surface mounting box (included)
- Type A rated to ensure tripping for residual a.c. currents and pulsating d.c. currents
- 13A fused spur with "passive" 30mA RCD protection at less than 40ms (typical)
- Complete with TEST button
- Twin earth terminals for easy cable connections
- Mechanical latching (no need to reset after power loss)

GENERAL INFORMATION

Colour / Finish	Grey	Application	Internal
Product Warranty	1 Year	Net Weight	0.55 kg

TECHNICAL INFORMATION

Construction Materials Line 1	Steel	Dimensions - Height	86 mm
Dimensions - Width	45 mm	Dimensions - Depth	146 mm



Product Code	Description	Item Barcode
TWSARCDMC	Twin Unswitched Metal Clad A Rated RCD Socket	5013845000147

PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	605 g
Intermediate Carton Depth (mm)	170 mm
Intermediate Carton Width (mm)	300 mm
Intermediate Carton Height (mm)	105 mm
Intermediate Pack Qty.	5
Pallet Layer Qty	180
Pallet Layers	5
Pallet Qty	900
MOM / OPQ	1 / 30

CE

UK
CA